

2-Butoxyethyl acetate

Version number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	2-Butoxyethyl acetate
Registration number (REACH)	01-2119475112-47-xxxx
EC number	203-933-3
Index number in CLP Annex VI	607-038-00-2
CAS number	112-07-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Solvent
--------------------------	---------

1.3 Details of the supplier of the safety data sheet

FRIEDRICH SCHARR KG
Liebknechtstraße 50
70565 Stuttgart
Germany

Telephone: +49 711 7868-0
Telefax: +49 711 7868-489
e-mail: info@scharr.de
Website: www.scharr.de

e-mail (competent person) produktsicherheit@scharr.de

1.4 Emergency telephone number

Poison centre			
Country	Name	Postal code/city	Telephone
Germany	Giftinformation Freiburg	79106 Freiburg im Breisgau	+49 (0)761 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Hazard class	Category	Hazard class and category	Hazard statement
acute toxicity (oral)	4	Acute Tox. 4	H302
acute toxicity (dermal)	4	Acute Tox. 4	H312
acute toxicity (inhal.)	4	Acute Tox. 4	H332

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- signal word warning

2-Butoxyethyl acetate

Version number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

- pictograms

GHS07



- hazard statements

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

- precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/....
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTRE/doctor if you feel unwell.
P321 Specific treatment (see on this label).
P330 Rinse mouth.
P501 Dispose of contents/container to industrial combustion plant.

2.3 Other hazards

This material is combustible, but will not ignite readily.

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance 2-butoxyethyl acetate
Identifiers
REACH Reg. No 01-2119475112-47-xxxx
EC No 203-933-3
CAS No 112-07-2
Index No 607-038-00-2

Specific Conc. Limits	M-Factors	ATE	Exposure route
-	-	1.880 mg/kg 1.500 mg/kg 11 mg/l/4h	oral dermal inhalation: vapour

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Self-protection of the first aider.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

2-Butoxyethyl acetate

Version number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulties. Headache. Vertigo.

4.3 Indication of any immediate medical attention and special treatment needed

Subsequent observance for pneumonia and pulmonary oedema. Supervise the blood circulation.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂), Sand

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Danger of bursting container.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Ventilate affected area. Avoidance of ignition sources.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Provision of sufficient ventilation.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

2-Butoxyethyl acetate

Version number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

- ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted.

- Lagerklasse (storage class according to TRGS 510, 10 (combustible liquids) Germany)

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)								
Country	Name of substance	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Source
AT	2-butoxyethyl acetate	112-07-2	MAK	20	133	40 (30 min)	270 (30 min)	GKV
CH	2-butoxyethyl acetate	112-07-2	MAK	10	66	20	132	SUVA
DE	2-butoxyethyl acetate	112-07-2	MAK	10	66	20	132	DFG
DE	2-butoxyethyl acetate	112-07-2	AGW	10	65	20	130	TRGS 900

2-Butoxyethyl acetate

Version number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of substance	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Source
EU	2-butoxyethyl acetate	112-07-2	IOELV	20	133	50	333	2000/39/EC

Notation

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values

Country	Name of agent	Parameter	Notation	Identifier	Value	Source
CH	2-butoxyethyl acetate	2-butoxyacetic acid	hydr, crea	BAT	150 mg/g	SUVA
DE	2-butoxyethyl acetate	2-butoxyacetic acid	hydr	BAT	150 mg/l	DFG
DE	2-butoxyethyl acetate	2-butoxyacetic acid	hydr, crea	BLV	150 mg/l	TRGS 903

Notation

crea creatinine
hydr hydrolysis

Human health values

Relevant DNELs and other threshold levels

Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	133 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	333 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
DNEL	169 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
DNEL	120 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects

Environmental values

Relevant PNECs and other threshold levels

End-point	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	60 mg/kg	aquatic organisms	water	short-term (single instance)
PNEC	0,56 mg/l	aquatic organisms	water	intermittent release
PNEC	0,304 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0,03 mg/l	aquatic organisms	marine water	short-term (single instance)

2-Butoxyethyl acetate

Version number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

Relevant PNECs and other threshold levels				
End-point	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	90 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	2,03 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0,203 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PNEC	0,415 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- type of material

PE: polyethylene, CR: chloroprene (chlorobutadiene) rubber, IIR: isobutene-isoprene (butyl) rubber

- material thickness

> 0,35 mm

- breakthrough times of the glove material

0,4 mm

>120 minutes (permeation: level 4)

- other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

[In case of inadequate ventilation] wear respiratory protection. Combination filtering device (EN 141). Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

2-Butoxyethyl acetate

Version number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	-63,5 °C at 1 atm
Boiling point or initial boiling point and boiling range	192,3 °C at 1 atm
Evaporation rate	not determined
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	1,3 vol% - 6,8 vol%
Flash point	78 °C at 1.013 hPa
Auto-ignition temperature	375 °C
pH (value)	4 (in aqueous solution: 10 g/l, 20 °C)
Kinematic viscosity	3,063 mm ² /s at 0 °C

Solubility(ies)

Water solubility	15 g/l at 20 °C
------------------	-----------------

Partition coefficient

Partition coefficient n-octanol/water (log value)	1,51 (pH value: 7, 25 °C)
---	---------------------------

Vapour pressure	0,375 mmHg at 25 °C
-----------------	---------------------

Density and/or relative density

Density	942,2 kg/m ³ at 20 °C
---------	----------------------------------

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

9.2 Other information

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant
--	--

2-Butoxyethyl acetate

Version number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

Other safety characteristics

Temperature class (EU, acc. to ATEX)

T2 (maximum permissible surface temperature on the equipment: 300°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

- acute toxicity estimate (ATE)

Oral	1.880 mg/kg
Dermal	1.500 mg/kg
Inhalation: vapour	11 mg/l/4h

Acute toxicity			
Exposure route	Endpoint	Value	Species
oral	LD50	1.880 mg/kg	rat
dermal	LD50	1.500 mg/kg	rabbit

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

2-Butoxyethyl acetate

Version number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment.
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 1, slightly hazardous to water (Germany)

Aquatic toxicity (acute)			
Endpoint	Value	Species	Exposure time
LC50	<40 mg/l	fish	96 h
EC50	145 mg/l	aquatic invertebrates	24 h
ErC50	1.570 mg/l	algae	72 h

Aquatic toxicity (chronic)			
Endpoint	Value	Species	Exposure time
EC50	145 mg/l	aquatic invertebrates	24 h

12.2 Persistence and degradability

Biodegradation

The substance is readily biodegradable. The relevant substances of the mixture are readily biodegradable. Data are not available.

Process of degradability		
Process	Degradation rate	Time
oxygen depletion	3 %	1 d

2-Butoxyethyl acetateVersion number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

12.3 Bioaccumulative potential

Data are not available.

n-octanol/water (log KOW)	1,51 (pH value: 7, 25 °C)
---------------------------	---------------------------

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

12.6 Endocrine disrupting propertiesDoes not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.**12.7 Other adverse effects**

Data are not available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

- | | |
|---|---|
| 14.1 UN number or ID number | not subject to transport regulations |
| 14.2 UN proper shipping name | not relevant |
| 14.3 Transport hazard class(es) | none |
| 14.4 Packing group | not assigned |
| 14.5 Environmental hazards | non-environmentally hazardous acc. to the dangerous goods regulations |
| 14.6 Special precautions for user | There is no additional information. |
| 14.7 Maritime transport in bulk according to IMO instruments | The cargo is not intended to be carried in bulk. |

2-Butoxyethyl acetate

Version number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - additional information

Not subject to ADR, RID and ADN.

International Maritime Dangerous Goods Code (IMDG) - additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	No
2-butoxyethyl acetate	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3

Legend

- R3
- Shall not be used in:
 - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 - tricks and jokes,
 - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
 - Articles not complying with paragraph 1 shall not be placed on the market.
 - Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
 - can be used as fuel in decorative oil lamps for supply to the general public, and
 - present an aspiration hazard and are labelled with H304.
 - Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
 - Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
 - lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";
 - grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage';
 - lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.;

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

not listed

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
	not assigned		

2-Butoxyethyl acetate

Version number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

Industrial Emissions Directive (IED)

VOC content	100 %
-------------	-------

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

not listed

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

not listed

Regulation on persistent organic pollutants (POP)

not listed

National regulations (Germany)

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK 1 slightly hazardous to water
(water hazard class)

Index number 592

Technical instructions on air quality control (Germany)

Number	Group of substances	Class	Conc.	Mass flow	Mass concentration	Notation
5.2.5	organic substances		≥ 25 wt%	0,5 kg/h	50 mg/m ³	3)

Notation

3) a total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m³, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed

2-Butoxyethyl acetate

Version number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

Country	Inventory	Status
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)
1.1		Index number in CLP Annex VI: 607-038-00-2
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.
3.1		Index No: 607-038-00-2
8.2	Type of material: IIR: isobutene-isoprene (butyl) rubber	Type of material: PE: polyethylene, CR: chloroprene (chlorobutadiene) rubber, IIR: isobutene-isoprene (butyl) rubber
8.2	Material thickness: > 0,7 mm	Material thickness: > 0,35 mm
8.2	Breakthrough times of the glove material: 0,4 mm >480 minutes (permeation: level 6)	Breakthrough times of the glove material: 0,4 mm >120 minutes (permeation: level 4)
8.2	Protective gloves Splash protection	
8.2	Type of material: IIR: isobutene-isoprene (butyl) rubber nitrile	

2-Butoxyethyl acetate

Version number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

Section	Former entry (text/value)	Actual entry (text/value)
8.2	Respiratory protection: [In case of inadequate ventilation] wear respiratory protection. Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown).	Respiratory protection: [In case of inadequate ventilation] wear respiratory protection. Combination filtering device (EN 141). Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).
12.5	Results of PBT and vPvB assessment: Data are not available.	Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.
12.6	Endocrine disrupting properties: Not listed.	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
AGW	Workplace exposure limit
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DFG	Deutsche Forschungsgemeinschaft MAK-und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
GKV	Grenzwerteverordnung
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)

2-Butoxyethyl acetate

Version number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

Abbr.	Descriptions of used abbreviations
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
SUVA	Grenzwerte am Arbeitsplatz, Suva
SVHC	Substance of Very High Concern
TRGS	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany)
TRGS 900	Arbeitsplatzgrenzwerte (TRGS 900)
TRGS 903	Biologische Grenzwerte (TRGS 903)
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.

2-Butoxyethyl acetate

Version number: 8.0
Replaces version of: 07.07.2022 (7)

Revision: 18.03.2024

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.