

**Spezialbenzin 30/75 S**Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name	<b>Spezialbenzin 30/75 S</b>
Registration number (REACH)	Not relevant (mixture)

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses	Industrial use
--------------------------	----------------

**1.3 Details of the supplier of the safety data sheet**

FRIEDRICH SCHARR KG  
Liebknechtstraße 50  
70565 Stuttgart  
Germany

Telephone: +49 711 7868-0  
Telefax: +49 711 7868-489  
e-mail: info@scharr.de  
Website: www.scharr.de

e-mail (competent person)	produktsicherheit@scharr.de (Produktsicherheit)
---------------------------	---

**1.4 Emergency telephone number**

Emergency information service	+49 711 7868-237 This number is only available during the following office hours: Mon-Fri 07:00 - 17:00
-------------------------------	--

Poison centre			
Country	Name	Postal code/city	Telephone
Germany	Giftinformation Freiburg	79106 Freiburg im Breisgau	+49 (0)761 19240

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 (CLP)

Hazard class	Category	Hazard class and category	Hazard statement
flammable liquid	2	Flam. Liq. 2	H225
skin corrosion/irritation	2	Skin Irrit. 2	H315
specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
aspiration hazard	1	Asp. Tox. 1	H304
hazardous to the aquatic environment - chronic hazard	2	Aquatic Chronic 2	H411

For full text of abbreviations: see SECTION 16.

**The most important adverse physicochemical, human health and environmental effects**

The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

## Spezialbenzin 30/75 S

Version number: 2.0  
 Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- signal word                      danger

- pictograms

GHS02, GHS07,  
 GHS08, GHS09



- hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

- precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.

- hazardous ingredients for labelling                      pentane, Hydrocarbons, C6, isoalkanes, <5% n-hexane, Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

### 2.3 Other hazards

of no significance

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)


### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
pentane	CAS No 109-66-0  EC No 203-692-4  Index No 601-006-00-1  REACH Reg. No 01-2119459286-30-xxxx	50 – < 75	Flam. Liq. 1 / H224 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	EC No 931-254-9  REACH Reg. No 01-2119484651-34-xxxx	25 – < 50	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	

**Spezialbenzin 30/75 S**Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	EC No 926-605-8  REACH Reg. No 01-2119486291-36-xxxx	10 – < 25	Flam. Liq. 2 / H225 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	

For full text of abbreviations: see SECTION 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

## General notes

Do not leave affected person unattended. Remove victim out of the danger area. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Self-protection of the first aider.

## Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

## Following skin contact

Wash with plenty of soap and water.

## Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

## Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

Narcotic effects. Breathing difficulties. Headache. Vertigo.

**4.3 Indication of any immediate medical attention and special treatment needed**

Subsequent observance for pneumonia and pulmonary oedema. Supervise the blood circulation.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

## Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>), Sand

## Unsuitable extinguishing media

Water jet

**5.2 Special hazards arising from the substance or mixture**

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Danger of bursting container.

## Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

## Spezialbenzin 30/75 S

Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Provision of sufficient ventilation.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Recommendations

- measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

## Spezialbenzin 30/75 S

Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- specific designs for storage rooms or vessels

- Lagerklasse (storage class according to TRGS 510, 3 (flammable and desensitizing explosive liquids) Germany)

- packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)								
Country	Name of substance	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Source
AT	pentane	109-66-0	MAK	600	1.800			GKV
CH	pentane	109-66-0	MAK	600	1.800	1.200	3.600	SUVA
DE	pentane	109-66-0	AGW	1.000	3.000	2.000	6.000	TRGS 900
EU	pentane	109-66-0	IOELV	1.000	3.000			2006/15/EC

Notation

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours

time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
pentane	109-66-0	DNEL	3.000 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
pentane	109-66-0	DNEL	432 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

## Spezialbenzin 30/75 S

Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Hydrocarbons, C6, isoalkanes, <5% n-hexane		DNEL	5.306 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C6, isoalkanes, <5% n-hexane		DNEL	13.964 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane		DNEL	5.306 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane		DNEL	13.964 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
pentane	109-66-0	PNEC	880 µg/l	aquatic organisms	water	intermittent release
pentane	109-66-0	PNEC	230 µg/l	aquatic organisms	freshwater	short-term (single instance)
pentane	109-66-0	PNEC	230 µg/l	aquatic organisms	marine water	short-term (single instance)
pentane	109-66-0	PNEC	3.600 µg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
pentane	109-66-0	PNEC	1,2 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
pentane	109-66-0	PNEC	1,2 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
pentane	109-66-0	PNEC	0,55 mg/kg	terrestrial organisms	soil	short-term (single instance)

### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

## Spezialbenzin 30/75 S

Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

- type of material  
NBR: acrylonitrile-butadiene rubber
- material thickness  
0,4 mm
- breakthrough times of the glove material  
>240 minutes (permeation: level 5)
- protective gloves - splash protection  
Type of material nitrile
- other protection measures  
Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.  
Wash hands thoroughly after handling.

### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	-153,6 °C at 101,3 kPa
Boiling point or initial boiling point and boiling range	>36 °C
Evaporation rate	not determined
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	1 vol% - 8,3 vol%
Flash point	<0 °C (ASTM D-56)
Auto-ignition temperature	200 °C
pH (value)	not determined
Kinematic viscosity	0,3 – 1,4 mm <sup>2</sup> /s at 20 °C (ASTM D7042)
Solubility(ies)	not determined

### Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

**Spezialbenzin 30/75 S**Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

Vapour pressure	40 hPa at 20 °C
-----------------	-----------------

## Density and/or relative density

Density	0,65 – 0,68 g/cm <sup>3</sup> at 20 °C
---------	--

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

**9.2 Other information**

Information with regard to physical hazard classes	there is no additional information
--	------------------------------------

## Other safety characteristics

Solid content	0 %
Temperature class (EU, acc. to ATEX)	T4 (maximum permissible surface temperature on the equipment: 135°C)

**SECTION 10: Stability and reactivity****10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

**10.2 Chemical stability**

See below "Conditions to avoid".

**10.3 Possibility of hazardous reactions**

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

**10.4 Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

**10.5 Incompatible materials**

Oxidisers

**10.6 Hazardous decomposition products**

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.



## Spezialbenzin 30/75 S

Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

##### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

##### Classification according to GHS (1272/2008/EC, CLP)

##### Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful in contact with skin or if inhaled.

Acute toxicity			
Exposure route	Endpoint	Value	Species
oral	LD50	>5.840 mg/kg	rat
dermal	LD50	>2.920 mg/kg	rabbit
inhalation: vapour	LC50	>25,2 mg/l/4h	rat

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
pentane	109-66-0	oral	LD50	>5.000 mg/kg	rat
pentane	109-66-0	inhalation: vapour	LC50	>25,3 mg/l/4h	rat

##### Skin corrosion/irritation

Causes skin irritation.

##### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

##### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

##### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

##### Carcinogenicity

Shall not be classified as carcinogenic.

##### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

##### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

##### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

## Spezialbenzin 30/75 S

Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

### Aspiration hazard

May be fatal if swallowed and enters airways.

### 11.2 Information on other hazards

There is no additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

Acc. to 1272/2008/EC: Toxic to aquatic life with long lasting effects.

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 2, obviously hazardous to water (Germany)

Aquatic toxicity (acute)			
Endpoint	Value	Species	Exposure time
EC50	2,7 mg/l	daphnia magna	48 h
EC50	10,7 mg/l	algae	72 h
LC50	4,26 mg/l	rainbow trout (Oncorhynchus mykiss)	96 h

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
pentane	109-66-0	EC50	2,8 mg/l	aquatic invertebrates	48 h
pentane	109-66-0	LL50	27,55 mg/l	fish	96 h
pentane	109-66-0	EL50	48,11 mg/l	aquatic invertebrates	48 h
Hydrocarbons, C6, isoalkanes, <5% n-hexane		LL50	18,27 mg/l	fish	96 h
Hydrocarbons, C6, isoalkanes, <5% n-hexane		EL50	31,9 mg/l	aquatic invertebrates	48 h
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane		LL50	12 mg/l	fish	96 h
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane		EL50	17,06 mg/l	aquatic invertebrates	48 h

### Biodegradation

Data are not available.

## Spezialbenzin 30/75 S

Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

### 12.2 Persistence and degradability

Degradability of components of the mixture						
Name of sub- stance	CAS No	Process	Degradation rate	Time	Method	Source
pentane	109-66-0	oxygen deple- tion	3 %	7 d		ECHA
Hydrocarbons, C6, isoalkanes, <5% n-hexane		oxygen deple- tion	83 %	10 d		ECHA
Hydrocarbons, C6-C7, isoalkanes, cyc- lics, <5% n-hex- ane		oxygen deple- tion	83 %	10 d		ECHA

### 12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
pentane	109-66-0	171	3,45 (pH value: 7, 25 °C)	
Hydrocarbons, C6, isoalkanes, <5% n-hexane		501,2	3,6 (pH value: 7, 20 °C)	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane		≥35,8 – ≤552	3,6 (pH value: 7, 20 °C)	

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Endocrine disrupting properties

Information on this property is not available.

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagegings

It is a dangerous waste; only packagegings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

## Spezialbenzin 30/75 S

Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

### Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR/RID/ADN	UN 3295
IMDG-Code	UN 3295
ICAO-TI	UN 3295

### 14.2 UN proper shipping name

ADR/RID/ADN	HYDROCARBONS, LIQUID, N.O.S.
IMDG-Code	HYDROCARBONS, LIQUID, N.O.S.
ICAO-TI	Hydrocarbons, liquid, n.o.s.

### 14.3 Transport hazard class(es)

ADR/RID/ADN	3
IMDG-Code	3
ICAO-TI	3

### 14.4 Packing group

ADR/RID/ADN	II
IMDG-Code	II
ICAO-TI	II

### 14.5 Environmental hazards

	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	pentane

### 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

### 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

### Information for each of the UN Model Regulations

#### Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - additional information

Classification code	F1
Danger label(s)	3, fish and tree



Environmental hazards	yes (hazardous to the aquatic environment)
-----------------------	--

## Spezialbenzin 30/75 S

Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

Special provisions (SP)	640D
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D/E
Hazard identification No	33

### International Maritime Dangerous Goods Code (IMDG) - additional information

Marine pollutant	yes (hazardous to the aquatic environment) (pentane)
Danger label(s)	3, fish and tree



Special provisions (SP)	-
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, S-D
Stowage category	B

### International Civil Aviation Organization (ICAO-IATA/DGR) - additional information

Environmental hazards	yes (hazardous to the aquatic environment)
Danger label(s)	3



Special provisions (SP)	A3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

##### VOC Deco-Paint Directive 2004/42/EC

VOC content	50 %
-------------	------

##### Industrial Emissions Directive (IED)

VOC content	100 %
-------------	-------

#### National regulations (Austria)

Ordinance on combustible liquids (VbF)

- VbF (group and hazard class) AI (combustible liquids of group A, hazard class I)

#### National regulations (Germany)

## Spezialbenzin 30/75 S

Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

### Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK 2 obviously hazardous to water  
(water hazard class)

### National regulations Switzerland

### Ordinance on the incentive tax on volatile organic compounds (VOCV)

VOC content (object of taxation). 100 %.

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)
2.3	Other hazards	Other hazards: of no significance
2.3	Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	
3.2		Description of the mixture: change in the listing (table)
11.1		Acute toxicity of components of the mixture: change in the listing (table)
11.2		Information on other hazards: There is no additional information.
12.3		Bioaccumulative potential of components of the mixture: change in the listing (table)
12.6	Other adverse effects: Data are not available.	Endocrine disrupting properties: Information on this property is not available.
14.1	UN number: 3295	UN number or ID number
14.1		ADR/RID/ADN: UN 3295
14.1		IMDG-Code: UN 3295
14.1		ICAO-TI: UN 3295
14.2	UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.	UN proper shipping name
14.2		ADR/RID/ADN: HYDROCARBONS, LIQUID, N.O.S.
14.2		IMDG-Code: HYDROCARBONS, LIQUID, N.O.S.
14.2		ICAO-TI: Hydrocarbons, liquid, n.o.s.

## Spezialbenzin 30/75 S

Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

Section	Former entry (text/value)	Actual entry (text/value)
14.3	Class: 3 (flammable liquids) (environmentally hazardous)	
14.3		ADR/RID/ADN: 3
14.3		IMDG-Code: 3
14.3		ICAO-TI: 3
14.4	Packing group: II (substance presenting medium danger)	Packing group
14.4		ADR/RID/ADN: II
14.4		IMDG-Code: II
14.4		ICAO-TI: II
14.7	UN number: 3295	
14.7	Proper shipping name: HYDROCARBONS, LIQUID, N.O.S.	
14.7	Class: 3	
14.7	Packing group: II	
14.7	UN number: 3295	
14.7	Proper shipping name: HYDROCARBONS, LIQUID, N.O.S.	
14.7	Class: 3	
14.7	Packing group: II	
14.7	Marine pollutant: yes (hazardous to the aquatic environment)	Marine pollutant: yes (hazardous to the aquatic environment) (pentane)
14.7	UN number: 3295	
14.7	Proper shipping name: Hydrocarbons, liquid, n.o.s.	
14.7	Class: 3	
14.7	Packing group: II	

## Spezialbenzin 30/75 S

Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
ADR/RID/ADN	European Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN)
AGW	Workplace exposure limit
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
GKV	Grenzwerteverordnung
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code



## Spezialbenzin 30/75 S

Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

Abbr.	Descriptions of used abbreviations
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
SUVA	Grenzwerte am Arbeitsplatz, Suva
TRGS	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany)
TRGS 900	Arbeitsplatzgrenzwerte (TRGS 900)
TWA	Time-weighted average
VbF	Ordinance on combustible liquids (Austria)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Spezialbenzin 30/75 S**

Version number: 2.0  
Replaces version of: 04.02.2020 (1)

Revision: 01.06.2021

**List of relevant phrases (code and full text as stated in chapter 2 and 3)**

Code	Text
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

**Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.