

Testbenzin 145/200

Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance **Testbenzin 145/200**
Registration number (REACH) 01-2119458049-33-xxxx
EC number 919-446-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Solvent

1.3 Details of the supplier of the safety data sheet

FRIEDRICH SCHARR KG
Liebknechtstraße 50
70565 Stuttgart
Germany

Telephone: +49 711 7868-0
Telefax: +49 711 7868-489
e-mail: info@scharr.de
Website: www.scharr.de

e-mail (competent person) produktsicherheit@scharr.de

1.4 Emergency telephone number

| Poison centre | | | |
|---------------|--------------------------|----------------------------|------------------|
| Country | Name | Postal code/city | Telephone |
| Germany | Giftinformation Freiburg | 79106 Freiburg im Breisgau | +49 (0)761 19240 |

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

| Hazard class | Category | Hazard class and category | Hazard statement |
|---|----------|---------------------------|------------------|
| flammable liquid | 3 | Flam. Liq. 3 | H226 |
| specific target organ toxicity - single exposure (narcotic effects, drowsiness) | 3 | STOT SE 3 | H336 |
| specific target organ toxicity - repeated exposure | 1 | STOT RE 1 | H372 |
| aspiration hazard | 1 | Asp. Tox. 1 | H304 |
| hazardous to the aquatic environment - chronic hazard | 2 | Aquatic Chronic 2 | H411 |

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

Testbenzin 145/200Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- signal word danger

- pictograms

GHS02, GHS07, GHS08,
GHS09

- hazard statements

| | |
|------|---|
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H336 | May cause drowsiness or dizziness. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |

- precautionary statements

| | |
|-----------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor. |
| P331 | Do NOT induce vomiting. |
| P370+P378 | In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403+P235 | Store in a well-ventilated place. Keep cool. |

- supplemental hazard information

| | |
|--------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
|--------|---|

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

| | |
|-------------------|---|
| Name of substance | Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) |
| Identifiers | |
| REACH Reg. No | 01-2119458049-33-xxxx |
| EC No | 919-446-0 |

SECTION 4: First aid measures**4.1 Description of first aid measures**

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Self-protection of the first aider.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Testbenzin 145/200

Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects. Breathing difficulties. Headache. Vertigo.

4.3 Indication of any immediate medical attention and special treatment needed

Subsequent observance for pneumonia and pulmonary oedema. Supervise the blood circulation.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂), Sand

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Danger of bursting container.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Ventilate affected area. Avoidance of ignition sources.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Provision of sufficient ventilation.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

Testbenzin 145/200

Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Lagerklasse (storage class according to TRGS 510, 3 (flammable and desensitizing explosive liquids) Germany)

Testbenzin 145/200

Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

- packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Occupational exposure limit values (Workplace Exposure Limits) | | | | | | | | |
|--|---|--------|------------|-----------|--------------------------|------------|---------------------------|----------|
| Country | Name of substance | CAS No | Identifier | TWA [ppm] | TWA [mg/m ³] | STEL [ppm] | STEL [mg/m ³] | Source |
| DE | Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | | AGW | | 300 | | 600 | TRGS 900 |

Notation

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours
time-weighted average (unless otherwise specified)

Human health values

| Relevant DNELs and other threshold levels | | | | |
|---|-----------------------|------------------------------------|-------------------|----------------------------|
| Endpoint | Threshold level | Protection goal, route of exposure | Used in | Exposure time |
| DNEL | 330 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| DNEL | 570 mg/m ³ | human, inhalatory | worker (industry) | acute - systemic effects |
| DNEL | 21 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Testbenzin 145/200

Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

Skin protection

- hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- type of material

Nitrile

- material thickness 0,38 mm

- breakthrough times of the glove material 0,4 mm

>480 minutes (permeation: level 6)

- other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

[In case of inadequate ventilation] wear respiratory protection. Combination filtering device (EN 141). Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|--|
| Physical state | liquid |
| Colour | colourless |
| Odour | characteristic |
| Melting point/freezing point | not determined |
| Boiling point or initial boiling point and boiling range | 145 – 200 °C |
| Evaporation rate | not determined |
| Flammability | flammable liquid in accordance with GHS criteria |
| Lower and upper explosion limit | 0,6 vol% - 7 vol% |
| Flash point | 38,5 °C at 1 atm |
| Auto-ignition temperature | >200 °C at 1 atm |
| pH (value) | not determined |
| Kinematic viscosity | 1,2 mm ² /s at 20 °C |

Testbenzin 145/200Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

| | |
|-----------------|----------------|
| Solubility(ies) | not determined |
|-----------------|----------------|

Partition coefficient

| | |
|---|-----------------------------------|
| Partition coefficient n-octanol/water (log value) | this information is not available |
|---|-----------------------------------|

| | |
|-----------------|--------------------|
| Vapour pressure | 0,231 kPa at 20 °C |
|-----------------|--------------------|

Density and/or relative density

| | |
|---------|---------------------------------|
| Density | 0,78 g/cm ³ at 15 °C |
|---------|---------------------------------|

| | |
|--------------------------|-----------------------|
| Particle characteristics | not relevant (liquid) |
|--------------------------|-----------------------|

9.2 Other information

| | |
|--|------------------------------------|
| Information with regard to physical hazard classes | there is no additional information |
|--|------------------------------------|

Other safety characteristics

| | |
|--------------------------------------|--|
| Surface tension | 24,7 mN/m (25 °C) |
| Temperature class (EU, acc. to ATEX) | T3 (maximum permissible surface temperature on the equipment: 200°C) |

SECTION 10: Stability and reactivity**10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". It's a reactive substance. The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Testbenzin 145/200

Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Classification according to GHS (1272/2008/EC, CLP)****Acute toxicity**

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful in contact with skin.

| Acute toxicity | | | |
|--------------------|----------|---------------|---------|
| Exposure route | Endpoint | Value | Species |
| dermal | LD50 | >3.400 mg/kg | rabbit |
| oral | LD50 | >15.000 mg/kg | rat |
| inhalation: vapour | LC50 | >13,1 mg/l/4h | rat |

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

Other information

Repeated exposure may cause skin dryness or cracking.

Testbenzin 145/200

Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Acc. to 1272/2008/EC: Toxic to aquatic life with long lasting effects.

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 2, hazardous to water (Germany)

| Aquatic toxicity (acute) | | | |
|--------------------------|----------|-----------------------|---------------|
| Endpoint | Value | Species | Exposure time |
| LL50 | 30 mg/l | fish | 96 h |
| EL50 | 22 mg/l | aquatic invertebrates | 48 h |
| ErC50 | 1,2 mg/l | algae | 96 h |

| Aquatic toxicity (chronic) | | | |
|----------------------------|------------|-----------------------|---------------|
| Endpoint | Value | Species | Exposure time |
| EL50 | 1,19 mg/l | aquatic invertebrates | 21 d |
| EC50 | 0,328 mg/l | aquatic invertebrates | 21 d |

12.2 Persistence and degradability

Biodegradation

The substance is readily biodegradable. The relevant substances of the mixture are readily biodegradable. Data are not available.

| Process of degradability | | |
|--------------------------|------------------|------|
| Process | Degradation rate | Time |
| oxygen depletion | 13,8 % | 4 d |

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

12.6 Endocrine disrupting properties

Information on this property is not available.

12.7 Other adverse effects

Data are not available.

Testbenzin 145/200Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information**14.1 UN number or ID number**

| | |
|-------------|---------|
| ADR/RID/ADN | UN 1300 |
| IMDG-Code | UN 1300 |
| ICAO-TI | UN 1300 |

14.2 UN proper shipping name

| | |
|-------------|-----------------------|
| ADR/RID/ADN | TURPENTINE SUBSTITUTE |
| IMDG-Code | TURPENTINE SUBSTITUTE |
| ICAO-TI | Turpentine substitute |

14.3 Transport hazard class(es)

| | |
|-------------|---|
| ADR/RID/ADN | 3 |
| IMDG-Code | 3 |
| ICAO-TI | 3 |

14.4 Packing group

| | |
|-------------|-----|
| ADR/RID/ADN | III |
| IMDG-Code | III |
| ICAO-TI | III |

14.5 Environmental hazards

hazardous to the aquatic environment

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Testbenzin 145/200

Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - additional information

Classification code F1
Danger label(s) 3, fish and tree



Environmental hazards yes (hazardous to the aquatic environment)
Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L
Transport category (TC) 3
Tunnel restriction code (TRC) D/E
Hazard identification No 30

International Maritime Dangerous Goods Code (IMDG) - additional information

Marine pollutant yes (hazardous to the aquatic environment)
Danger label(s) 3, fish and tree



Special provisions (SP) 223
Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L
EmS F-E, S-E
Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - additional information

Environmental hazards yes (hazardous to the aquatic environment)
Danger label(s) 3



Special provisions (SP) A3
Excepted quantities (EQ) E1
Limited quantities (LQ) 10 L

Testbenzin 145/200

Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

not listed

Seveso Directive

| 2012/18/EU (Seveso III) | | | |
|-------------------------|--|---|-------|
| No | Dangerous substance/hazard categories | Qualifying quantity (tonnes) for the application of lower and upper-tier requirements | Notes |
| E2 | environmental hazards (hazardous to the aquatic environment, cat. 2) | 200 500 | 57) |

Notation

57) hazardous to the Aquatic Environment in category Chronic 2

Industrial Emissions Directive (IED)

| | |
|-------------|-------|
| VOC content | 100 % |
|-------------|-------|

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Regulation on persistent organic pollutants (POP)

not listed

National regulations (Austria)

Ordinance on combustible liquids (VbF)

- VbF (group and hazard class) AII (combustible liquids of group A, hazard class II)

National regulations (Germany)

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK 2 hazardous to water
(water hazard class)

Index number 775

Technical instructions on air quality control (Germany)

Testbenzin 145/200

Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

| Number | Group of substances | Class | Conc. | Mass flow | Mass concentration | Notation |
|--------|---------------------|---------|----------|-----------|----------------------|----------|
| 5.2.5 | organic substances | class I | ≥ 25 wt% | 0,1 kg/h | 20 mg/m ³ | 3) |

Notation

3) a total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m³, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

National regulations Switzerland

Ordinance on the incentive tax on volatile organic compounds (VOCV)

VOC content (object of taxation): 100 %
2710.1991 (petroleum)

National inventories

| Country | Inventory | Status |
|---------|------------|---------------------|
| AU | AIIC | substance is listed |
| CA | DSL | substance is listed |
| CN | IECSC | substance is listed |
| EU | ECSI | substance is listed |
| EU | REACH Reg. | substance is listed |
| KR | KECI | substance is listed |
| MX | INSQ | substance is listed |
| NZ | NZIoC | substance is listed |
| PH | PICCS | substance is listed |
| TR | CICR | substance is listed |
| TW | TCSI | substance is listed |
| US | TSCA | substance is listed |

Legend

| | |
|------------|---|
| AIIC | Australian Inventory of Industrial Chemicals |
| CICR | Chemical Inventory and Control Regulation |
| DSL | Domestic Substances List (DSL) |
| ECSI | EC Substance Inventory (EINECS, ELINCS, NLP) |
| IECSC | Inventory of Existing Chemical Substances Produced or Imported in China |
| INSQ | National Inventory of Chemical Substances |
| KECI | Korea Existing Chemicals Inventory |
| NZIoC | New Zealand Inventory of Chemicals |
| PICCS | Philippine Inventory of Chemicals and Chemical Substances (PICCS) |
| REACH Reg. | REACH registered substances |
| TCSI | Taiwan Chemical Substance Inventory |
| TSCA | Toxic Substance Control Act |

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance.

Testbenzin 145/200

Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

SECTION 16: Other information

Indication of changes (revised safety data sheet)

| Section | Former entry (text/value) | Actual entry (text/value) |
|---------|--|---|
| 8.2 | Respiratory protection: [In case of inadequate ventilation] wear respiratory protection. Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown). | Respiratory protection: [In case of inadequate ventilation] wear respiratory protection. Combination filtering device (EN 141). Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown). |
| 12.5 | Results of PBT and vPvB assessment: Data are not available. | Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB. |
| 12.6 | Endocrine disrupting properties: Not listed. | Endocrine disrupting properties: Information on this property is not available. |

Abbreviations and acronyms

| Abbr. | Descriptions of used abbreviations |
|-------------|---|
| ADN | Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) |
| ADR | Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road) |
| ADR/RID/ADN | Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN) |
| AGW | Workplace exposure limit |
| CAS | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances) |
| CLP | Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures |
| DGR | Dangerous Goods Regulations (see IATA/DGR) |
| DNEL | Derived No-Effect Level |
| EC50 | Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval |
| EC No | The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union) |
| EINECS | European Inventory of Existing Commercial Chemical Substances |
| EL50 | Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms |
| ELINCS | European List of Notified Chemical Substances |
| EmS | Emergency Schedule |
| ErC50 | ≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control |
| GHS | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations |
| IATA | International Air Transport Association |

Testbenzin 145/200

Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

| Abbr. | Descriptions of used abbreviations |
|-----------|---|
| IATA/DGR | Dangerous Goods Regulations (DGR) for the air transport (IATA) |
| ICAO | International Civil Aviation Organization |
| ICAO-TI | Technical instructions for the safe transport of dangerous goods by air |
| IMDG | International Maritime Dangerous Goods Code |
| IMDG-Code | International Maritime Dangerous Goods Code |
| LC50 | Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval |
| LD50 | Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval |
| LL50 | Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality |
| NLP | No-Longer Polymer |
| PBT | Persistent, Bioaccumulative and Toxic |
| ppm | Parts per million |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals |
| RID | Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail) |
| STEL | Short-term exposure limit |
| SVHC | Substance of Very High Concern |
| TRGS | Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany) |
| TRGS 900 | Arbeitsplatzgrenzwerte (TRGS 900) |
| TWA | Time-weighted average |
| VbF | Ordinance on combustible liquids (Austria) |
| VOC | Volatile Organic Compounds |
| vPvB | Very Persistent and very Bioaccumulative |

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

| Code | Text |
|------|---|
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H336 | May cause drowsiness or dizziness. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |

Testbenzin 145/200

Version number: 9.0
Replaces version of: 07.11.2022 (8)

Revision: 13.11.2023

| Code | Text |
|------|--|
| H411 | Toxic to aquatic life with long lasting effects. |

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.