

Testbenzin 180/210

Version number: 4.0
Replaces version of: 17.08.2021 (3)

Revision: 05.04.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	Testbenzin 180/210
Registration number (REACH)	01-2119473977-17-xxxx
EC number	919-164-8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Industrial use
--------------------------	----------------

1.3 Details of the supplier of the safety data sheet

FRIEDRICH SCHARR KG
Liebknechtstraße 50
70565 Stuttgart
Germany

Telephone: +49 711 7868-0
Telefax: +49 711 7868-489
e-mail: info@scharr.de
Website: www.scharr.de

e-mail (competent person)	produktsicherheit@scharr.de
---------------------------	-----------------------------

1.4 Emergency telephone number

Poison centre			
Country	Name	Postal code/city	Telephone
Germany	Giftinformation Freiburg	79106 Freiburg im Breisgau	+49 (0)761 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Hazard class	Category	Hazard class and category	Hazard statement
specific target organ toxicity - repeated exposure	1	STOT RE 1	H372
aspiration hazard	1	Asp. Tox. 1	H304
hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- signal word danger

Testbenzin 180/210Version number: 4.0
Replaces version of: 17.08.2021 (3)

Revision: 05.04.2022

- pictograms

GHS08

**- hazard statements**

H304	May be fatal if swallowed and enters airways.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

- precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P501	Dispose of contents/container to industrial combustion plant.

- supplemental hazard information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3 Other hazards

This material is combustible, but will not ignite readily.

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Name of substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
Identifiers	
REACH Reg. No	01-2119473977-17-xxxx
EC No	919-164-8

SECTION 4: First aid measures**4.1 Description of first aid measures****General notes**

Do not leave affected person unattended. Remove victim out of the danger area. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Self-protection of the first aider.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Testbenzin 180/210

Version number: 4.0
Replaces version of: 17.08.2021 (3)

Revision: 05.04.2022

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulties. Headache. Vertigo.

4.3 Indication of any immediate medical attention and special treatment needed

Subsequent observance for pneumonia and pulmonary oedema. Supervise the blood circulation.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂), Sand

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Danger of bursting container.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Ventilate affected area. Avoidance of ignition sources.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Provision of sufficient ventilation.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

Testbenzin 180/210

Version number: 4.0
Replaces version of: 17.08.2021 (3)

Revision: 05.04.2022

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

- Lagerklasse (storage class according to TRGS 510, 10 (combustible liquids) Germany)

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)								
Country	Name of substance	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Source
AT	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		MAK	20		40 (30 min)		GKV
CH	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		MAK	100	525			SUVA
DE	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		AGW		50		100	TRGS 900

Notation

STEL

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

Testbenzin 180/210

Version number: 4.0
Replaces version of: 17.08.2021 (3)

Revision: 05.04.2022

Notation

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours
time-weighted average (unless otherwise specified)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- type of material

NBR: acrylonitrile-butadiene rubber, FKM: fluoro-elastomer

- material thickness

NBR 0,4 mm FKM 0,7 mm

- breakthrough times of the glove material

0,4 mm

>480 minutes (permeation: level 6)

- other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	-57 °C at 1 atm
Boiling point or initial boiling point and boiling range	185 – 215 °C at 1 atm
Evaporation rate	not determined
Flammability	this material is combustible, but will not ignite readily

Testbenzin 180/210

Version number: 4.0
Replaces version of: 17.08.2021 (3)

Revision: 05.04.2022

Lower and upper explosion limit	0,6 vol% - 7 vol%
Flash point	66 °C at 1 atm
Auto-ignition temperature	>200 °C at 1 atm
pH (value)	not determined
Kinematic viscosity	1,74 mm ² /s at 20 °C

Solubility(ies)

Water solubility	6,4 mg/l
------------------	----------

Partition coefficient

Partition coefficient n-octanol/water (log value)	4,2
Soil organic carbon/water (log KOC)	3,5

Vapour pressure	0,05 kPa at 20 °C
-----------------	-------------------

Density and/or relative density

Density	0,805 g/cm ³ at 15 °C
---------	----------------------------------

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

9.2 Other information

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant
--	--

Other safety characteristics

Surface tension	25,9 mN/m (25 °C)
Temperature class (EU, acc. to ATEX)	T3 (maximum permissible surface temperature on the equipment: 200°C)

Testbenzin 180/210Version number: 4.0
Replaces version of: 17.08.2021 (3)

Revision: 05.04.2022

SECTION 10: Stability and reactivity**10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Classification according to GHS (1272/2008/EC, CLP)****Acute toxicity**

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful in contact with skin.

Acute toxicity			
Exposure route	Endpoint	Value	Species
dermal	LD50	>3.400 mg/kg	rabbit
oral	LD50	>15.000 mg/kg	rat
inhalation: vapour	LC50	>13,1 mg/l/4h	rat

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Testbenzin 180/210

Version number: 4.0
Replaces version of: 17.08.2021 (3)

Revision: 05.04.2022

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

Other information

Repeated exposure may cause skin dryness or cracking.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Acc. to 1272/2008/EC: Harmful to aquatic life with long lasting effects.
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 2, obviously hazardous to water (Germany)

Aquatic toxicity (acute)			
Endpoint	Value	Species	Exposure time
LL50	30 mg/l	fish	96 h
EL50	22 mg/l	aquatic invertebrates	48 h
ErC50	0,94 mg/l	algae	72 h
EC50	0,53 mg/l	algae	72 h

Aquatic toxicity (chronic)			
Endpoint	Value	Species	Exposure time
EL50	1,19 mg/l	aquatic invertebrates	21 d
EC50	0,328 mg/l	aquatic invertebrates	21 d

Biodegradation

The substance is readily biodegradable. The relevant substances of the mixture are readily biodegradable. Data are not available.

12.2 Persistence and degradability

Process of degradability		
Process	Degradation rate	Time
oxygen depletion	13,8 %	4 d

12.3 Bioaccumulative potential

Data are not available.

Testbenzin 180/210

Version number: 4.0
Replaces version of: 17.08.2021 (3)

Revision: 05.04.2022

n-octanol/water (log KOW)	4,2
BCF	105 (ECHA)

12.4 Mobility in soil

The Organic Carbon normalised adsorption coefficient	3,5 (ECHA)
--	------------

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Not listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number or ID number	not subject to transport regulations
14.2 UN proper shipping name	not relevant
14.3 Transport hazard class(es)	none
14.4 Packing group	not assigned
14.5 Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6 Special precautions for user	There is no additional information.
14.7 Maritime transport in bulk according to IMO instruments	The cargo is not intended to be carried in bulk.

Testbenzin 180/210

Version number: 4.0
Replaces version of: 17.08.2021 (3)

Revision: 05.04.2022

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - additional information

Not subject to ADR, RID and ADN.

International Maritime Dangerous Goods Code (IMDG) - additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

not listed

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
	not assigned		

VOC Deco-Paint Directive 2004/42/EC

VOC content	100 %
-------------	-------

Industrial Emissions Directive (IED)

VOC content	100 %
-------------	-------

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Regulation on persistent organic pollutants (POP)

Not listed.

National regulations (Austria)

Ordinance on combustible liquids (VbF)

- VbF (group and hazard class) AIII (combustible liquids of group A, hazard class III)

National regulations (Germany)

Testbenzin 180/210

Version number: 4.0
Replaces version of: 17.08.2021 (3)

Revision: 05.04.2022

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK 2 obviously hazardous to water
(water hazard class)

15.1.3. Technical instructions on air quality control (Germany)

2

Number	Group of substances	Class	Conc.	Mass flow	Mass concentration	Notation
5.2.5	organic substances	class I	≥ 25 wt%	0,1 kg/h	20 mg/m ³	3)

Notation

3) a total mass flow of 0.50 kg/h or a total mass concentration of 50 mg/m³, each of which to be indicated as total carbon, shall not be exceeded (except organic particulate matter)

National regulations Switzerland

Ordinance on the incentive tax on volatile organic compounds (VOCV)

VOC content (object of taxation): 100 %
2710.1991 (petroleum (mainly non-aromatic hydrocarbon mixtures))

National inventories

Country	Inventory	Status
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed

Legend

ECSI EC Substance Inventory (EINECS, ELINCS, NLP)
REACH Reg. REACH registered substances

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)
8.2	Breakthrough times of the glove material: >480 minutes (permeation: level 6)	Breakthrough times of the glove material: 0,4 mm >480 minutes (permeation: level 6)

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
AGW	Workplace exposure limit
BCF	Bioconcentration factor

Testbenzin 180/210

Version number: 4.0
Replaces version of: 17.08.2021 (3)

Revision: 05.04.2022

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DGR	Dangerous Goods Regulations (see IATA/DGR)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
GKV	Grenzwerteverordnung
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
SUVA	Grenzwerte am Arbeitsplatz, Suva
SVHC	Substance of Very High Concern
TRGS	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany)
TRGS 900	Arbeitsplatzgrenzwerte (TRGS 900)
TWA	Time-weighted average
VbF	Ordinance on combustible liquids (Austria)
VOC	Volatile Organic Compounds

Testbenzin 180/210

Version number: 4.0
Replaces version of: 17.08.2021 (3)

Revision: 05.04.2022

Abbr.	Descriptions of used abbreviations
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H304	May be fatal if swallowed and enters airways.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.