

**Petroleum**

<b>Synonyms</b>	Aliphatisches, cycloaliphatisches und aromatisches Kohlenwasserstoffgemisch
<b>Appearance</b>	colourless
<b>Odour</b>	characteristic

**Delivery specification**

properties	method	min. limit value	max. limit value	unit
Density (15 °C)	DIN 51 757	0,785	0,820	kg/liter
Refractive index (20 °C)	DIN 51 423	1,437	1,451	-----
Content of water	DIN 51 777	-----	0,05	%
Boiling range (1013 hPa)	ASTM D1078	140	260	°C
Flash point (Abel/Pensky)	DIN 51 755	61	-----	°C
Aromatics content	UV/VIS (UOP 495)	-----	20	%
Benzene content	GC	-----	5	ppm

**Further parameters**

Properties	Method	Value	Unit
Pt/Co color value	DIN EN ISO 6271	max. 10	-----
Anilinpunkt	DIN ISO 2977	62	°C
kinematic viscosity (20 °C)	-----	2,0	mm <sup>2</sup> /s

date of compilation 2021-05-26

No liability is assumed for the correctness and completeness of the information in this product information. The data provided are for guidance only. It is the user's responsibility to use the products with caution and to observe the applicable laws and regulations. Our general terms of delivery, in particular the liability provisions contained therein, apply to all deliveries. Subject to change. The specified data however does not release you from your obligation to inspect the incoming goods. Die angegebenen Daten entbinden Sie jedoch nicht von Ihrer Obliegenheit zur Wareneingangskontrolle.