

## Xylol vergällt (Butylacetat)

Version number: 1.0

Date of compilation: 25.05.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **Xylol vergällt (Butylacetat)**  
Registration number (REACH) Not relevant (mixture)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Solvents

#### 1.3 Details of the supplier of the safety data sheet

FRIEDRICH SCHARR KG  
Liebknechtstraße 50  
70565 Stuttgart  
Germany

Telephone: +49 711 7868-0  
Telefax: +49 711 7868-489  
e-mail: info@scharr.de  
Website: www.scharr.de

e-mail (competent person) produktsicherheit@scharr.de (Produktsicherheit)

#### 1.4 Emergency telephone number

Emergency information service +49 711 7868-237  
This number is only available during the following office hours: Mon-Fri 07:00 - 17:00

Poison centre			
Country	Name	Postal code/city	Telephone
Germany	Giftinformation Freiburg	79106 Freiburg im Breisgau	+49 (0)761 19240

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Hazard class	Category	Hazard class and category	Hazard statement
flammable liquid	3	Flam. Liq. 3	H226
acute toxicity (dermal)	4	Acute Tox. 4	H312
acute toxicity (inhal.)	4	Acute Tox. 4	H332
skin corrosion/irritation	2	Skin Irrit. 2	H315
serious eye damage/eye irritation	2	Eye Irrit. 2	H319
specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335
specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16.

## Xylol vergällt (Butylacetat)

Version number: 1.0

Date of compilation: 25.05.2021

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- signal word danger

- pictograms

GHS02, GHS07, GHS08



- hazard statements

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H312+H332 Harmful in contact with skin or if inhaled.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.

- precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P331 Do NOT induce vomiting.  
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 Store in a well-ventilated place. Keep cool.

- hazardous ingredients for labelling xylene

### 2.3 Other hazards

of no significance

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures



Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
xylene	EC No 905-588-0  REACH Reg. No 01-2119488216-32- xxxx	≥ 90	Flam. Liq. 3 / H226 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 STOT RE 2 / H373 Asp. Tox. 1 / H304	

## Xylol vergällt (Butylacetat)

Version number: 1.0

Date of compilation: 25.05.2021

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
n-butyl acetate	CAS No 123-86-4  EC No 204-658-1  REACH Reg. No 01-2119485493-29- xxxx	5 – < 10	Flam. Liq. 3 / H226 STOT SE 3 / H336	 

Name of substance	Specific Conc. Limits	M-Factors	ATE	Exposure route
xylene	-	-	1.100 mg/kg 11 mg/l/4h	dermal inhalation: vapour

For full text of abbreviations: see SECTION 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Self-protection of the first aider.

##### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

##### Following skin contact

Wash with plenty of soap and water.

##### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulties. Headache. Vertigo.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Subsequent observance for pneumonia and pulmonary oedema. Supervise the blood circulation.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>), Sand

##### Unsuitable extinguishing media

Water jet

## Xylol vergällt (Butylacetat)

Version number: 1.0

Date of compilation: 25.05.2021

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Danger of bursting container.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Provision of sufficient ventilation.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Recommendations

- measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

## Xylol vergällt (Butylacetat)

Version number: 1.0

Date of compilation: 25.05.2021

### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Managing of associated risks

##### - explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

##### - flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

##### - ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

##### - specific designs for storage rooms or vessels

- Lagerklasse (storage class according to TRGS 510, 3 (flammable and desensitizing explosive liquids) Germany)

##### - packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)								
Country	Name of substance	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Source
AT	xylene	100-41-4	MAK	100	440			GKV
AT	xylene	108-88-3	MAK	50	190	100	380	GKV
AT	n-butyl acetate	123-86-4	MAK	100	480			GKV
CH	xylene	100-41-4	MAK	50	220	50	220	SUVA
CH	xylene	108-88-3	MAK	50	190	200	760	SUVA
CH	n-butyl acetate	123-86-4	MAK	100	480	200	960	SUVA
DE			AGW		100		200	TRGS 900
DE	xylene	100-41-4	MAK	20	88	40	176	DFG
DE	xylene	100-41-4	AGW	20	88	40	176	TRGS 900
DE	xylene	108-88-3	MAK	50	190	100	380	DFG
DE	xylene	108-88-3	AGW	50	190	200	760	TRGS 900

## Xylol vergällt (Butylacetat)

Version number: 1.0

Date of compilation: 25.05.2021

### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of substance	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Source
DE	n-butyl acetate	123-86-4	MAK	100	480	200	960	DFG
DE	n-butyl acetate	123-86-4	AGW	62	300	124	600	TRGS 900
EU	xylene	100-41-4	IOELV	100	442	200	884	2000/39/EC
EU	xylene	108-88-3	IOELV	50	192	100	384	2006/15/EC
EU	n-butyl acetate	123-86-4	IOELV	50	241	150	723	2019/1831/EU

#### Notation

STEL

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours  
time-weighted average (unless otherwise specified)

### Biological limit values

Country	Name of agent	Parameter	Notation	Identifier	Value	Source
AT	xylene	methylhippuric acids		BGW	1,5 g/l	VGÜ
AT	xylene	xylene		BGW	1 mg/l	VGÜ
CH	xylene, mixture of isomers	methylhippuric acids		BAT	2 g/l	SUVA
DE	xylene, mixture of isomers	methylhippuric acids		BLV	2.000 mg/l	TRGS 903

### Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
xylene		DNEL	221 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
xylene		DNEL	442 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
xylene		DNEL	221 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
xylene		DNEL	442 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
xylene		DNEL	212 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
n-butyl acetate	123-86-4	DNEL	600 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
n-butyl acetate	123-86-4	DNEL	600 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects

## Xylol vergällt (Butylacetat)

Version number: 1.0

Date of compilation: 25.05.2021

### Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
n-butyl acetate	123-86-4	DNEL	300 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
n-butyl acetate	123-86-4	DNEL	300 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects

### Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
xylene		PNEC	0,327 mg/l	aquatic organisms	water	intermittent release
xylene		PNEC	0,327 mg/l	aquatic organisms	freshwater	short-term (single instance)
xylene		PNEC	0,327 mg/l	aquatic organisms	marine water	short-term (single instance)
xylene		PNEC	6,58 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
xylene		PNEC	12,46 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
xylene		PNEC	12,46 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
xylene		PNEC	2,31 mg/kg	terrestrial organisms	soil	short-term (single instance)
n-butyl acetate	123-86-4	PNEC	0,18 mg/l	aquatic organisms	freshwater	short-term (single instance)
n-butyl acetate	123-86-4	PNEC		aquatic organisms	freshwater	short-term (single instance)
n-butyl acetate	123-86-4	PNEC	0,018 mg/l	aquatic organisms	marine water	short-term (single instance)
n-butyl acetate	123-86-4	PNEC	35,6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
n-butyl acetate	123-86-4	PNEC	0,981 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
n-butyl acetate	123-86-4	PNEC	0,0981 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
n-butyl acetate	123-86-4	PNEC	0,0903 mg/kg	terrestrial organisms	soil	short-term (single instance)
n-butyl acetate	123-86-4	PNEC	0,36 mg/l	aquatic organisms	water	intermittent release

## 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

**Xylol vergällt (Butylacetat)**

Version number: 1.0

Date of compilation: 25.05.2021

**Individual protection measures (personal protective equipment)****Eye/face protection**

Wear eye/face protection.

**Skin protection****- hand protection**

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**- other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

**Environmental exposure controls**

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	<-90 °C
Boiling point or initial boiling point and boiling range	126 °C at 1.013 hPa
Evaporation rate	not determined
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	1 vol% - 8 vol%
Flash point	>23 °C
Auto-ignition temperature	415 °C
pH (value)	not determined
Solubility(ies)	not determined

**Partition coefficient**

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

**Xylol vergällt (Butylacetat)**

Version number: 1.0

Date of compilation: 25.05.2021

Vapour pressure	15 hPa at 20 °C
-----------------	-----------------

## Density and/or relative density

Density	not determined
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

**9.2 Other information**

Information with regard to physical hazard classes	there is no additional information
--	------------------------------------

## Other safety characteristics

Solid content	0 %
Temperature class (EU, acc. to ATEX)	T2 (maximum permissible surface temperature on the equipment: 300°C)

**SECTION 10: Stability and reactivity****10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

**10.2 Chemical stability**

See below "Conditions to avoid".

**10.3 Possibility of hazardous reactions**

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

**10.4 Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

**10.5 Incompatible materials**

Oxidisers

**10.6 Hazardous decomposition products**

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## Xylol vergällt (Butylacetat)

Version number: 1.0

Date of compilation: 25.05.2021

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

##### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

##### Classification according to GHS (1272/2008/EC, CLP)

##### Acute toxicity

Harmful in contact with skin. Harmful if inhaled.

##### - acute toxicity estimate (ATE)

Dermal 1.170 mg/kg  
Inhalation: vapour 11,7 mg/l/4h

##### Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
xylene		dermal	1.100 mg/kg
xylene		inhalation: vapour	11 mg/l/4h

##### Skin corrosion/irritation

Causes skin irritation.

##### Serious eye damage/eye irritation

Causes serious eye irritation.

##### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

##### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

##### Carcinogenicity

Shall not be classified as carcinogenic.

##### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

##### Specific target organ toxicity - single exposure

May cause respiratory irritation.

##### Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

##### Aspiration hazard

May be fatal if swallowed and enters airways.

#### 11.2 Information on other hazards

There is no additional information.

## Xylol vergällt (Butylacetat)

Version number: 1.0

Date of compilation: 25.05.2021

### SECTION 12: Ecological information

#### 12.1 Toxicity

Acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment.  
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 2, obviously hazardous to water (Germany)

##### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
xylene		LC50	8,4 mg/l	fish	96 h
xylene		EC50	4,9 mg/l	algae	72 h
xylene		ErC50	4,7 mg/l	algae	72 h
n-butyl acetate	123-86-4	LC50	18 mg/l	fish	96 h
n-butyl acetate	123-86-4	EC50	18 mg/l	fish	96 h
n-butyl acetate	123-86-4	ErC50	335 mg/l	algae	24 h

##### Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
xylene		EL50	2,9 mg/l	aquatic invertebrates	21 d
xylene		ErC50	4,36 mg/l	algae	73 h
xylene		EC50	2,2 mg/l	algae	73 h
n-butyl acetate	123-86-4	EC50	34,2 mg/l	aquatic invertebrates	21 d
n-butyl acetate	123-86-4	LC50	43,5 mg/l	aquatic invertebrates	21 d

#### Biodegradation

Data are not available.

#### 12.2 Persistence and degradability

Data are not available.

#### 12.3 Bioaccumulative potential

Data are not available.

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

Data are not available.

#### 12.6 Endocrine disrupting properties

Information on this property is not available.

#### 12.7 Other adverse effects

Data are not available.

**Xylol vergällt (Butylacetat)**

Version number: 1.0

Date of compilation: 25.05.2021

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

**Relevant provisions relating to waste**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**Remarks**

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

**SECTION 14: Transport information****14.1 UN number or ID number**

ADR/RID/ADN	UN 1993
IMDG-Code	UN 1993
ICAO-TI	UN 1993

**14.2 UN proper shipping name**

ADR/RID/ADN	FLAMMABLE LIQUID, N.O.S.
IMDG-Code	FLAMMABLE LIQUID, N.O.S.
ICAO-TI	Flammable liquid, n.o.s.
Technical name (Hazardous ingredients)	xylene, n-butyl acetate

**14.3 Transport hazard class(es)**

ADR/RID/ADN	3
IMDG-Code	3
ICAO-TI	3

**14.4 Packing group**

ADR/RID/ADN	III
IMDG-Code	III
ICAO-TI	III

**14.5 Environmental hazards**

non-environmentally hazardous acc. to the dangerous goods regulations

**14.6 Special precautions for user**

Provisions for dangerous goods (ADR) should be complied within the premises.

**14.7 Maritime transport in bulk according to IMO instruments**

The cargo is not intended to be carried in bulk.

## Xylol vergällt (Butylacetat)

Version number: 1.0

Date of compilation: 25.05.2021

### Information for each of the UN Model Regulations

#### Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - additional information

Classification code F1

Danger label(s) 3



Special provisions (SP) 274, 601

Excepted quantities (EQ) E1

Limited quantities (LQ) 5 L

Transport category (TC) 3

Tunnel restriction code (TRC) D/E

Hazard identification No 30

#### International Maritime Dangerous Goods Code (IMDG) - additional information

Marine pollutant -

Danger label(s) 3



Special provisions (SP) 223, 274, 955

Excepted quantities (EQ) E1

Limited quantities (LQ) 5 L

EmS F-E, S-E

Stowage category A

#### International Civil Aviation Organization (ICAO-IATA/DGR) - additional information

Danger label(s) 3



Special provisions (SP) A3

Excepted quantities (EQ) E1

Limited quantities (LQ) 10 L

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Relevant provisions of the European Union (EU)

##### VOC Deco-Paint Directive 2004/42/EC

VOC content	100 %
-------------	-------

##### Industrial Emissions Directive (IED)

VOC content	100 %
-------------	-------

## Xylol vergällt (Butylacetat)

Version number: 1.0

Date of compilation: 25.05.2021

### National regulations (Austria)

Ordinance on combustible liquids (VbF)

- VbF (group and hazard class) AII (combustible liquids of group A, hazard class II)

### National regulations (Germany)

**Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)**

Wassergefährdungsklasse, WGK 2 obviously hazardous to water  
(water hazard class)

### National regulations Switzerland

**Ordinance on the incentive tax on volatile organic compounds (VOCV)**

VOC content (object of taxation): 100 %

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
2019/1831/EU	Commission Directive establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC
Acute Tox.	Acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
ADR/RID/ADN	European Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN)
AGW	Workplace exposure limit
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DFG	Deutsche Forschungsgemeinschaft MAK-und BAT-Werte-Liste, Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Wiley-VCH, Weinheim
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval

## Xylol vergällt (Butylacetat)

Version number: 1.0

Date of compilation: 25.05.2021

Abbr.	Descriptions of used abbreviations
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
GKV	Grenzwerteverordnung
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
SUVA	Grenzwerte am Arbeitsplatz, Suva

## Xylol vergällt (Butylacetat)

Version number: 1.0

Date of compilation: 25.05.2021

Abbr.	Descriptions of used abbreviations
TRGS	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany)
TRGS 900	Arbeitsplatzgrenzwerte (TRGS 900)
TRGS 903	Biologische Grenzwerte (TRGS 903)
TWA	Time-weighted average
VbF	Ordinance on combustible liquids (Austria)
VGÜ	Verordnung über die Gesundheitsüberwachung am Arbeitsplatz (VGÜ)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.