

**Bettbahnöl CGLP 32**Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name	<b>Bettbahnöl CGLP 32</b>
Registration number (REACH)	Not relevant (mixture)

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses	Lubricants, greases, release products
--------------------------	---------------------------------------

**1.3 Details of the supplier of the safety data sheet**

FRIEDRICH SCHARR KG  
Liebknechtstraße 50  
70565 Stuttgart  
Germany

Telephone: +49 711 7868-0  
Telefax: +49 711 7868-489  
e-mail: info@scharr.de  
Website: www.scharr.de

e-mail (competent person)	produktsicherheit@scharr.de
---------------------------	-----------------------------

**1.4 Emergency telephone number**

Poison centre			
Country	Name	Postal code/city	Telephone
Germany	Giftinformation Freiburg	79106 Freiburg im Breisgau	+49 (0)761 19240

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 (CLP)

Hazard class	Category	Hazard class and category	Hazard statement
hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

**2.2 Label elements**

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- |                     |                                                    |
|---------------------|----------------------------------------------------|
| - signal word       | not required                                       |
| - pictograms        | not required                                       |
| - hazard statements |                                                    |
| H412                | Harmful to aquatic life with long lasting effects. |

## Bettbahnöl CGLP 32

Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

### - precautionary statements

P273 Avoid release to the environment.  
P501 Dispose of contents/container to industrial combustion plant.

### - supplemental hazard information

EUH208 Contains Amine, C10-14-tert-Alkyl-. May produce an allergic reaction.

## 2.3 Other hazards

### Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of  $\geq 0,1\%$ .

### Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0,1\%$ .








## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

#### Hazardous ingredients

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Amine, C10-14-tert-Alkyl-	EC No 701-175-2  REACH Reg. No 01-2119456798-18- xxxx	< 1	Acute Tox. 4 / H302 Acute Tox. 3 / H311 Acute Tox. 2 / H330 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Skin Sens. 1A / H317 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	  
C16-18-(even numbered, saturated and unsaturated)-alkylamines	CAS No 1213789-63-9  EC No 627-034-4  REACH Reg. No 01-2119473797-19- xxxx	< 1	Acute Tox. 4 / H302 Skin Corr. 1B / H314 Eye Dam. 1 / H318 STOT SE 3 / H335 STOT RE 2 / H373 Asp. Tox. 1 / H304 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	   

Name of substance	Specific Conc. Limits	M-Factors	ATE	Exposure route
Amine, C10-14-tert-Alkyl-	-	-	>500 mg/kg 251 mg/kg 0,5 mg/l/4h	oral dermal inhalation: vapour
C16-18-(even numbered, saturated and unsaturated)-alkylamines	-	M-factor (acute) = 10 M-factor (chronic) = 10	1.689 mg/kg	oral

For full text of abbreviations: see SECTION 16.

## Bettbahnöl CGLP 32

Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Self-protection of the first aider.

##### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

##### Following skin contact

Wash with plenty of soap and water.

##### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulties. Headache. Vertigo.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Subsequent observance for pneumonia and pulmonary oedema. Supervise the blood circulation.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>), Sand

##### Unsuitable extinguishing media

Water jet

#### 5.2 Special hazards arising from the substance or mixture

Danger of bursting container.

##### Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## Bettbahnöl CGLP 32

Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Ventilate affected area. Avoidance of ignition sources.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Provision of sufficient ventilation.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Recommendations

- measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

- Lagerklasse (storage class according to TRGS 510, 10 (combustible liquids) Germany)

#### 7.3 Specific end use(s)

See section 16 for a general overview.

## Bettbahnöl CGLP 32

Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)  
this information is not available

##### Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Amine, C10-14-tert-Alkyl-		DNEL	12,5 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Amine, C10-14-tert-Alkyl-		DNEL	12,1 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	DNEL	0,38 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	DNEL	1 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	DNEL	1 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects

##### Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Amine, C10-14-tert-Alkyl-		PNEC	0,001 mg/l	aquatic organisms	freshwater	short-term (single instance)
Amine, C10-14-tert-Alkyl-		PNEC	0 mg/l	aquatic organisms	marine water	short-term (single instance)
Amine, C10-14-tert-Alkyl-		PNEC	0,635 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Amine, C10-14-tert-Alkyl-		PNEC	2,14 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Amine, C10-14-tert-Alkyl-		PNEC	0,214 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Amine, C10-14-tert-Alkyl-		PNEC	0,428 mg/kg	terrestrial organisms	soil	short-term (single instance)
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	PNEC	0,26 µg/l	aquatic organisms	freshwater	short-term (single instance)

**Bettbahnöl CGLP 32**

Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	PNEC	0,026 µg/l	aquatic organisms	marine water	short-term (single instance)
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	PNEC	550 µg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	PNEC	3,76 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	PNEC	0,376 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	PNEC	10 mg/kg	terrestrial organisms	soil	short-term (single instance)

## 8.2 Exposure controls

### Appropriate engineering controls

General ventilation.

### Individual protection measures (personal protective equipment)

#### Eye/face protection

Wear eye/face protection.

#### Skin protection

##### - hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### - type of material

PE: polyethylene, CR: chloroprene (chlorobutadiene) rubber, IIR: isobutene-isoprene (butyl) rubber

##### - material thickness

> 0,35 mm

##### - breakthrough times of the glove material

0,4 mm

>120 minutes (permeation: level 4)

##### - other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### Respiratory protection

[In case of inadequate ventilation] wear respiratory protection. Combination filtering device (EN 141). Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

**Bettbahnöl CGLP 32**Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

**Environmental exposure controls**

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

Physical state	liquid
Colour	yellowish brown
Odour	characteristic
Melting point/freezing point	<-10 °C at 1.013 hPa
Boiling point or initial boiling point and boiling range	≥207 °C at 101,3 kPa
Evaporation rate	not determined
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	0,6 vol% - 6,5 vol%
Flash point	>200 °C
Auto-ignition temperature	not determined
pH (value)	not determined
Kinematic viscosity	32 mm <sup>2</sup> /s at 40 °C
Solubility(ies)	not determined

**Partition coefficient**

Partition coefficient n-octanol/water (log value)	this information is not available
---------------------------------------------------	-----------------------------------

Vapour pressure	<0,1 hPa at 20 °C
-----------------	-------------------

**Density and/or relative density**

Density	0,86 g/cm <sup>3</sup> at 15 °C
---------	---------------------------------

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

## Bettbahnöl CGLP 32

Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

### 9.2 Other information

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant
Other safety characteristics	there is no additional information

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

### 10.5 Incompatible materials

Oxidisers

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification according to GHS (1272/2008/EC, CLP)

##### Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Amine, C10-14-tert-Alkyl-		oral	>500 mg/kg
Amine, C10-14-tert-Alkyl-		dermal	251 mg/kg
Amine, C10-14-tert-Alkyl-		inhalation: vapour	0,5 mg/l/4h
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	oral	1.689 mg/kg



## Bettbahnöl CGLP 32

Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Amine, C10-14-tert-Alkyl-		oral	LD50	>500 mg/kg	rat
Amine, C10-14-tert-Alkyl-		dermal	LD50	251 mg/kg	rat
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	oral	LD50	1.689 mg/kg	rat
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	dermal	LD50	>2.000 mg/kg	rat

### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

### Respiratory or skin sensitisation

Contains Amine, C10-14-tert-Alkyl-. May produce an allergic reaction.

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Shall not be classified as carcinogenic.

### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## 11.2 Information on other hazards

There is no additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

Acc. to 1272/2008/EC: Harmful to aquatic life with long lasting effects.  
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 2, obviously hazardous to water (Germany)

## Bettbahnöl CGLP 32

Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Amine, C10-14-tert-Alkyl-		LC50	1,3 mg/l	fish	96 h
Amine, C10-14-tert-Alkyl-		EC50	≤6 mg/l	aquatic invertebrates	48 h
Amine, C10-14-tert-Alkyl-		ErC50	0,44 mg/l	algae	72 h
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	LC50	0,84 mg/l	fish	96 h
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	EC50	0,32 mg/l	aquatic invertebrates	48 h
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	ErC50	0,39 mg/l	algae	72 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Amine, C10-14-tert-Alkyl-		EC50	63,5 mg/l	microorganisms	30 min
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	EC50	0,24 mg/l	aquatic invertebrates	21 d

### 12.2 Persistence and degradability

#### Biodegradation

Data are not available.

Degradability of components of the mixture						
Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
Amine, C10-14-tert-Alkyl-		oxygen depletion	22 %	28 d		ECHA
C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9	carbon dioxide generation	18 %	6 d		ECHA

## Bettbahnöl CGLP 32

Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

Degradability of components of the mixture						
Name of sub- stance	CAS No	Process	Degradation rate	Time	Method	Source
C16-18-(even numbered, sat- urated and un- saturated)-al- kylamines	1213789-63-9	oxygen deple- tion	34 %	5 d		ECHA

### 12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Amine, C10-14-tert-Alkyl-			2,9 (pH value: ~7, 23 °C)	

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of  $\geq 0,1\%$ .

### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0,1\%$ .

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagegings

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

Mineral-based non-chlorinated engine, gear and lubricating oils 13 02 05\*

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

**Bettbahnöl CGLP 32**

Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

**SECTION 14: Transport information**

- 14.1 UN number or ID number** not subject to transport regulations
- 14.2 UN proper shipping name** not relevant
- 14.3 Transport hazard class(es)** none
- 14.4 Packing group** not assigned
- 14.5 Environmental hazards** non-environmentally hazardous acc. to the dangerous goods regulations
- 14.6 Special precautions for user**  
There is no additional information.
- 14.7 Maritime transport in bulk according to IMO instruments**  
The cargo is not intended to be carried in bulk.

**Information for each of the UN Model Regulations**

**Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - additional information**

Not subject to ADR, RID and ADN.

**International Maritime Dangerous Goods Code (IMDG) - additional information**

Not subject to IMDG.

**International Civil Aviation Organization (ICAO-IATA/DGR) - additional information**

Not subject to ICAO-IATA.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**Relevant provisions of the European Union (EU)**

**List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list**

none of the ingredients are listed

**Seveso Directive**

2012/18/EU (Seveso III)

No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
	not assigned		

**Industrial Emissions Directive (IED)**

VOC content 0,2996 %

**Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)**

none of the ingredients are listed

## Bettbahnöl CGLP 32

Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

### Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

### National regulations (Austria)

Ordinance on combustible liquids (VbF)

not applicable (mass fraction of liquids with a flash point of more than 100° C or of solids is higher than 30 %)

### National regulations (Germany)

#### Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK 2 obviously hazardous to water  
(water hazard class)

### National regulations Switzerland

#### Ordinance on the incentive tax on volatile organic compounds (VOCV)

VOC content (object of taxation): 97,7 %

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)
2.3	Other hazards: of no significance	Other hazards
2.3		Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0,1\%$ .
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0,1\%$ .
3.2		Hazardous ingredients: change in the listing (table)
8.1	Control parameters: This information is not available.	Control parameters: Occupational exposure limit values (Workplace Exposure Limits) this information is not available
8.2	Type of material: NBR: acrylonitrile-butadiene rubber	Type of material: PE: polyethylene, CR: chloroprene (chlorobutadiene) rubber, IIR: isobutene-isoprene (butyl) rubber
8.2	Material thickness: 0,4 mm	Material thickness: > 0,35 mm
8.2	Breakthrough times of the glove material: >240 minutes (permeation: level 5)	Breakthrough times of the glove material: 0,4 mm  >120 minutes (permeation: level 4)

# Safety Data Sheet

acc. to Regulation (EC) No. 1907/2006 (REACH),  
amended by 2020/878/EU

## Bettbahnöl CGLP 32

Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

Section	Former entry (text/value)	Actual entry (text/value)
8.2	Respiratory protection: In case of inadequate ventilation wear respiratory protection.	Respiratory protection: [In case of inadequate ventilation] wear respiratory protection. Combination filtering device (EN 141). Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).
12.5	Results of PBT and vPvB assessment: Data are not available.	Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of ≥ 0,1%.
12.6	Endocrine disrupting properties: None of the ingredients are listed.	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0,1%.

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye

# Safety Data Sheet

acc. to Regulation (EC) No. 1907/2006 (REACH),  
amended by 2020/878/EU

## Bettbahnöl CGLP 32

Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

Abbr.	Descriptions of used abbreviations
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
log KOW	n-Octanol/water
M-factor	Means a multiplying factor. It is applied to the concentration of a substance classified as hazardous to the aquatic environment acute category 1 or chronic category 1, and is used to derive by the summation method the classification of a mixture in which the substance is present
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitisation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
SVHC	Substance of Very High Concern
TRGS	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

**Bettbahnöl CGLP 32**

Version number: 2.0  
Replaces version of: 28.07.2021 (1)

Revision: 01.03.2023

**Classification procedure**

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**List of relevant phrases (code and full text as stated in section 2 and 3)**

Code	Text
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.