

Hydrauliköl HLP-D 32 ZF

Version number: 3.0
Replaces version of: 03.12.2019 (2)

Revision: 22.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **Hydrauliköl HLP-D 32 ZF**
Registration number (REACH) Not relevant (mixture)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Lubricants, greases, release products

1.3 Details of the supplier of the safety data sheet

FRIEDRICH SCHARR KG
Liebknechtstraße 50
70565 Stuttgart
Germany

Telephone: +49 711 7868-0
Telefax: +49 711 7868-489
e-mail: info@scharr.de
Website: www.scharr.de

e-mail (competent person) produktsicherheit@scharr.de (Produktsicherheit)

1.4 Emergency telephone number

Emergency information service +49 711 7868-237
This number is only available during the following office hours: Mon-Fri 07:00 - 17:00

Poison centre			
Country	Name	Postal code/city	Telephone
Austria	Vergiftungsinformationszentrale Poisons Information Centre	1090 Wien	+43 (0)1 406 43 43
Germany	Giftinformation Freiburg	79106 Freiburg im Breisgau	+49 (0)761 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Hazard class	Category	Hazard class and category	Hazard statement
hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects
Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- signal word not required
- pictograms not required

Hydrauliköl HLP-D 32 ZF

Version number: 3.0
Replaces version of: 03.12.2019 (2)

Revision: 22.02.2021

- hazard statements
H412 Harmful to aquatic life with long lasting effects.
- precautionary statements
P273 Avoid release to the environment.
P501 Dispose of contents/container to industrial combustion plant.

2.3 Other hazards

of no significance







SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Hazardous ingredients

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
2,6-di-tert-butylphenol	CAS No 128-39-2 EC No 204-884-0 REACH Reg. No 01-2119490822-33- xxxx 01-2119480422-43- xxxx	< 1	Skin Irrit. 2 / H315 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	 
Reference substance 001	CAS No 1213789-63-9 REACH Reg. No 01-2119473797-19- xxxx	< 1	Acute Tox. 4 / H302 Skin Corr. 1B / H314 Eye Dam. 1 / H318 STOT SE 3 / H335 STOT RE 2 / H373 Asp. Tox. 1 / H304 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	   

Name of substance	Specific Conc. Limits	M-Factors	ATE	Exposure route
Reference substance 001	-	M-factor (acute) = 10.0 M-factor (chronic) = 10.0	1.689 mg/kg	oral

For full text of abbreviations: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Self-protection of the first aider.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Hydrauliköl HLP-D 32 ZF

Version number: 3.0
Replaces version of: 03.12.2019 (2)

Revision: 22.02.2021

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulties. Headache. Vertigo.

4.3 Indication of any immediate medical attention and special treatment needed

Subsequent observance for pneumonia and pulmonary oedema. Supervise the blood circulation.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂), Sand

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Danger of bursting container.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂), Phosphorus oxides (P_xO_y), Sulphur dioxide (SO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Provision of sufficient ventilation.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Hydrauliköl HLP-D 32 ZF

Version number: 3.0
Replaces version of: 03.12.2019 (2)

Revision: 22.02.2021

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

- specific designs for storage rooms or vessels

- Recommended storage temperature 5 – 40 °C

- Lagerklasse (storage class according to TRGS 510, 10 (combustible liquids) Germany)

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

This information is not available.

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2,6-di-tert-butylphenol	128-39-2	DNEL	70,61 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2,6-di-tert-butylphenol	128-39-2	DNEL	11,25 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Reference substance 001	1213789-63-9	DNEL	0,38 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Reference substance 001	1213789-63-9	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
Reference substance 001	1213789-63-9	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	acute - local effects

Hydrauliköl HLP-D 32 ZF

Version number: 3.0
Replaces version of: 03.12.2019 (2)

Revision: 22.02.2021

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
2,6-di-tert-butyl-phenol	128-39-2	PNEC	60 mg/kg	aquatic organisms	water	short-term (single instance)
2,6-di-tert-butyl-phenol	128-39-2	PNEC	0,0045 mg/l	aquatic organisms	water	intermittent release
2,6-di-tert-butyl-phenol	128-39-2	PNEC	0,001 mg/l	aquatic organisms	freshwater	short-term (single instance)
2,6-di-tert-butyl-phenol	128-39-2	PNEC	0 mg/l	aquatic organisms	marine water	short-term (single instance)
2,6-di-tert-butyl-phenol	128-39-2	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2,6-di-tert-butyl-phenol	128-39-2	PNEC	0,317 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2,6-di-tert-butyl-phenol	128-39-2	PNEC	0,032 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2,6-di-tert-butyl-phenol	128-39-2	PNEC	0,697 mg/kg	terrestrial organisms	soil	short-term (single instance)
Reference substance 001	1213789-63-9	PNEC	0,26 µg/l	aquatic organisms	freshwater	short-term (single instance)
Reference substance 001	1213789-63-9	PNEC	0,026 µg/l	aquatic organisms	marine water	short-term (single instance)
Reference substance 001	1213789-63-9	PNEC	550 µg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Reference substance 001	1213789-63-9	PNEC	3,76 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Reference substance 001	1213789-63-9	PNEC	0,376 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Reference substance 001	1213789-63-9	PNEC	10 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- type of material

NBR: acrylonitrile-butadiene rubber

Hydrauliköl HLP-D 32 ZF

Version number: 3.0
Replaces version of: 03.12.2019 (2)

Revision: 22.02.2021

- material thickness 0,4 mm
- breakthrough times of the glove material
>240 minutes (permeation: level 5)
- protective gloves - splash protection
Type of material nitrile
- other protection measures
Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.
Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	light yellow
Odour	characteristic
Melting point/freezing point	<-10 °C
Boiling point or initial boiling point and boiling range	not determined
Evaporation rate	not determined
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	0,6 vol% - 6,5 vol%
Flash point	>200 °C
Auto-ignition temperature	>310 °C
pH (value)	not determined
Kinematic viscosity	32 mm ² /s at 40 °C
Solubility(ies)	not determined

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Hydrauliköl HLP-D 32 ZFVersion number: 3.0
Replaces version of: 03.12.2019 (2)

Revision: 22.02.2021

Vapour pressure	not determined
-----------------	----------------

Density and/or relative density

Density	0,859 g/cm ³ at 15 °C
---------	----------------------------------

Particle characteristics	no data available
--------------------------	-------------------

9.2 Other information

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant
--	--

Other safety characteristics

Temperature class (EU, acc. to ATEX)	T2 (maximum permissible surface temperature on the equipment: 300°C)
--------------------------------------	--

SECTION 10: Stability and reactivity**10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Hydrauliköl HLP-D 32 ZF

Version number: 3.0
Replaces version of: 03.12.2019 (2)

Revision: 22.02.2021

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Reference substance 001	1213789-63-9	oral	1.689 mg/kg

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Acc. to 1272/2008/EC: Harmful to aquatic life with long lasting effects.
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 2, obviously hazardous to water (Germany)

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2,6-di-tert-butylphenol	128-39-2	LC50	1,4 mg/l	fish	96 h
2,6-di-tert-butylphenol	128-39-2	EC50	0,45 mg/l	aquatic invertebrates	48 h
Reference substance 001	1213789-63-9	LC50	0,84 mg/l	fish	96 h
Reference substance 001	1213789-63-9	EC50	0,32 mg/l	aquatic invertebrates	48 h
Reference substance 001	1213789-63-9	ErC50	0,39 mg/l	algae	72 h

Hydrauliköl HLP-D 32 ZF

Version number: 3.0
Replaces version of: 03.12.2019 (2)

Revision: 22.02.2021

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2,6-di-tert-butylphenol	128-39-2	LC50	1,1 mg/l	fish	7 d
2,6-di-tert-butylphenol	128-39-2	EC50	0,14 mg/l	aquatic invertebrates	21 d
Reference substance 001	1213789-63-9	EC50	0,24 mg/l	aquatic invertebrates	21 d

Biodegradation

Data are not available.

12.2 Persistence and degradability

Degradability of components of the mixture						
Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
2,6-di-tert-butylphenol	128-39-2	oxygen depletion	≥12 – ≤24 %	28 d		ECHA
Reference substance 001	1213789-63-9	carbon dioxide generation	18 %	6 d		ECHA
Reference substance 001	1213789-63-9	oxygen depletion	34 %	5 d		ECHA

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
2,6-di-tert-butylphenol	128-39-2		4,5 (24 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Information on this property is not available.

12.7 Other adverse effects

Data are not available.

Hydrauliköl HLP-D 32 ZF

Version number: 3.0
Replaces version of: 03.12.2019 (2)

Revision: 22.02.2021

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

Mineral based non-chlorinated hydraulic oils 13 01 10*

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number or ID number

ADN

UN

14.2 UN proper shipping name

not assigned

14.3 Transport hazard class(es)

none

14.4 Packing group

not assigned

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - additional information

not assigned

International Maritime Dangerous Goods Code (IMDG) - additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - additional information

Not subject to ICAO-IATA.

Hydrauliköl HLP-D 32 ZF

Version number: 3.0
Replaces version of: 03.12.2019 (2)

Revision: 22.02.2021

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

VOC Deco-Paint Directive 2004/42/EC

VOC content	0,207 %
-------------	---------

Directive on industrial emissions (VOCs, 2010/75/EU)

VOC content	0,207 %
-------------	---------

National regulations (Austria)

Ordinance on combustible liquids (VbF) not applicable (mass fraction of liquids with a flash point of more than 100° C or of solids is higher than 30 %)

National regulations (Germany)

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK 2 obviously hazardous to water
(water hazard class)

National regulations Switzerland

Ordinance on the incentive tax on volatile organic compounds (VOCV)

The product is exempt from the tax. Product in which the VOC content does not exceed 3 per cent (% by weight).

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)
2.3	Other hazards	Other hazards: of no significance
2.3	Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	
3.2		Hazardous ingredients: change in the listing (table)
3.2		Hazardous ingredients: change in the listing (table)
8.2		Protective gloves Splash protection
8.2		Type of material: nitrile
11.2		Information on other hazards: There is no additional information.
12.6	Other adverse effects: Data are not available.	Endocrine disrupting properties: Information on this property is not available.

Hydrauliköl HLP-D 32 ZF

Version number: 3.0
Replaces version of: 03.12.2019 (2)

Revision: 22.02.2021

Section	Former entry (text/value)	Actual entry (text/value)
14.1	UN number: not subject to transport regulations	UN number or ID number
14.1		ADN: UN
14.2	UN proper shipping name: not relevant	UN proper shipping name: not assigned
14.3	Transport hazard class(es): not assigned	Transport hazard class(es): none
14.7	Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN): Not subject to ADR. Not subject to RID.	Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - additional information: not assigned
14.7	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (ADN)	
14.7	Identifier number: 9006	
14.7	Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	
14.7	Class: 9	
14.7	Number of cones/blue lights: 0	

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)

Hydrauliköl HLP-D 32 ZF

Version number: 3.0
Replaces version of: 03.12.2019 (2)

Revision: 22.02.2021

Abbr.	Descriptions of used abbreviations
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
log KOW	n-Octanol/water
M-factor	Means a multiplying factor. It is applied to the concentration of a substance classified as hazardous to the aquatic environment acute category 1 or chronic category 1, and is used to derive by the summation method the classification of a mixture in which the substance is present
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TRGS	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Hydrauliköl HLP-D 32 ZF

Version number: 3.0
Replaces version of: 03.12.2019 (2)

Revision: 22.02.2021

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.