

**Industrie-Getriebeöl CLP 320**

Version number: 1.0

Date of compilation: 01.06.2021

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name **Industrie-Getriebeöl CLP 320**  
Registration number (REACH) Not relevant (mixture)

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses Lubricants, greases, release products

**1.3 Details of the supplier of the safety data sheet**

FRIEDRICH SCHARR KG  
Liebknechtstraße 50  
70565 Stuttgart  
Germany

Telephone: +49 711 7868-0  
Telefax: +49 711 7868-489  
e-mail: info@scharr.de  
Website: www.scharr.de

e-mail (competent person) produktsicherheit@scharr.de (Produktsicherheit)

**1.4 Emergency telephone number**

Emergency information service +49 711 7868-237  
This number is only available during the following office hours: Mon-Fri 07:00 - 17:00

| Poison centre |                          |                            |                  |
|---------------|--------------------------|----------------------------|------------------|
| Country       | Name                     | Postal code/city           | Telephone        |
| Germany       | Giftinformation Freiburg | 79106 Freiburg im Breisgau | +49 (0)761 19240 |

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 (CLP)

| Hazard class  | Category | Hazard class and category | Hazard statement |
|---|----------|---------------------------|------------------|
| hazardous to the aquatic environment - chronic hazard | 3        | Aquatic Chronic 3         | H412             |

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

**2.2 Label elements**

Labelling according to Regulation (EC) No 1272/2008 (CLP)

- signal word not required
- pictograms not required
- hazard statements  
H412 Harmful to aquatic life with long lasting effects.

**Industrie-Getriebeöl CLP 320**

Version number: 1.0

Date of compilation: 01.06.2021

- precautionary statements

P273 Avoid release to the environment.  
P501 Dispose of contents/container to industrial combustion plant.

- supplemental hazard information

EUH208 Contains 2,5-Bis(oktyldithio)-1,3,4-Thiadiazol. May produce an allergic reaction.

**2.3 Other hazards**

of no significance

**SECTION 3: Composition/information on ingredients**

**3.1 Substances**

Not relevant (mixture)

**3.2 Mixtures**

Hazardous ingredients

| Name of substance                     | Identifier  | Wt% | Classification acc. to GHS  | Pictograms |
|---------------------------------------|---|-----|---|------------|
| 2,6-di-tert-butylphenol               | CAS No<br>128-39-2<br><br>EC No<br>204-884-0<br><br>REACH Reg. No<br>01-2119490822-33-<br>xxxx<br>01-2119480422-43-<br>xxxx | < 1 | Skin Irrit. 2 / H315<br>Aquatic Acute 1 / H400<br>Aquatic Chronic 1 / H410  |            |
| 2,5-Bis(oktyldithio)-1,3,4-Thiadiazol | CAS No<br>13539-13-4<br><br>EC No<br>236-912-2  | < 1 | Skin Irrit. 2 / H315<br>Eye Irrit. 2 / H319<br>Skin Sens. 1 / H317  |            |
| (Z)-octadec-9-enylamine               | CAS No<br>112-90-3<br><br>EC No<br>204-015-5<br><br>Index No<br>612-283-00-3  | < 1 | Acute Tox. 4 / H302<br>Skin Corr. 1B / H314<br>STOT SE 3 / H335<br>STOT RE 2 / H373<br>Asp. Tox. 1 / H304<br>Aquatic Acute 1 / H400<br>Aquatic Chronic 1 / H410 |            |

| Name of substance       | Specific Conc. Limits | M-Factors   | ATE       | Exposure route |
|-------------------------|-----------------------|---|-----------|----------------|
| (Z)-octadec-9-enylamine | -                     | M-factor<br>(acute) = 10.0<br>M-factor<br>(chronic) =<br>10.0 | 500 mg/kg | oral           |

For full text of abbreviations: see SECTION 16.

## Industrie-Getriebeöl CLP 320

Version number: 1.0

Date of compilation: 01.06.2021

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Self-protection of the first aider.

##### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

##### Following skin contact

Wash with plenty of soap and water.

##### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulties. Headache. Vertigo.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Subsequent observance for pneumonia and pulmonary oedema. Supervise the blood circulation.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>), Sand

##### Unsuitable extinguishing media

Water jet

#### 5.2 Special hazards arising from the substance or mixture

Danger of bursting container.

##### Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Phosphorus oxides (P<sub>x</sub>O<sub>y</sub>), Sulphur dioxide (SO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Remove persons to safety.

##### For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Provision of sufficient ventilation.

**Industrie-Getriebeöl CLP 320**

Version number: 1.0

Date of compilation: 01.06.2021

**6.2 Environmental precautions**

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

**6.3 Methods and material for containment and cleaning up**

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

**6.4 Reference to other sections**

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

Recommendations

- measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

**7.2 Conditions for safe storage, including any incompatibilities**

- specific designs for storage rooms or vessels

- Lagerklasse (storage class according to TRGS 510, 10 (combustible liquids) Germany)

**7.3 Specific end use(s)**

See section 16 for a general overview.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

This information is not available.

| Relevant DNELs of components of the mixture |          |           |                         |                                    |                   |                            |
|---|----------|-----------|-------------------------|------------------------------------|-------------------|----------------------------|
| Name of substance                           | CAS No   | End-point | Threshold level         | Protection goal, route of exposure | Used in           | Exposure time              |
| 2,6-di-tert-butylphenol                     | 128-39-2 | DNEL      | 70,61 mg/m <sup>3</sup> | human, inhalatory                  | worker (industry) | chronic - systemic effects |
| 2,6-di-tert-butylphenol                     | 128-39-2 | DNEL      | 11,25 mg/kg bw/day      | human, dermal                      | worker (industry) | chronic - systemic effects |

**Industrie-Getriebeöl CLP 320**

Version number: 1.0

Date of compilation: 01.06.2021

| Relevant PNECs of components of the mixture |          |           |                 |                       |                              |                              |
|---|----------|-----------|-----------------|-----------------------|------------------------------|------------------------------|
| Name of substance                           | CAS No   | End-point | Threshold level | Organism              | Environmental compartment    | Exposure time                |
| 2,6-di-tert-butylphenol                     | 128-39-2 | PNEC      | 60 mg/kg        | aquatic organisms     | water                        | short-term (single instance) |
| 2,6-di-tert-butylphenol                     | 128-39-2 | PNEC      | 0,0045 mg/l     | aquatic organisms     | water                        | intermittent release         |
| 2,6-di-tert-butylphenol                     | 128-39-2 | PNEC      | 0,001 mg/l      | aquatic organisms     | freshwater                   | short-term (single instance) |
| 2,6-di-tert-butylphenol                     | 128-39-2 | PNEC      | 0 mg/l          | aquatic organisms     | marine water                 | short-term (single instance) |
| 2,6-di-tert-butylphenol                     | 128-39-2 | PNEC      | 10 mg/l         | aquatic organisms     | sewage treatment plant (STP) | short-term (single instance) |
| 2,6-di-tert-butylphenol                     | 128-39-2 | PNEC      | 0,317 mg/kg     | aquatic organisms     | freshwater sediment          | short-term (single instance) |
| 2,6-di-tert-butylphenol                     | 128-39-2 | PNEC      | 0,032 mg/kg     | aquatic organisms     | marine sediment              | short-term (single instance) |
| 2,6-di-tert-butylphenol                     | 128-39-2 | PNEC      | 0,697 mg/kg     | terrestrial organisms | soil                         | short-term (single instance) |

**8.2 Exposure controls**

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- type of material

NBR: acrylonitrile-butadiene rubber

- material thickness

0,4 mm

- breakthrough times of the glove material

>240 minutes (permeation: level 5)

- protective gloves - splash protection

Type of material nitrile

- other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

**Industrie-Getriebeöl CLP 320**

Version number: 1.0

Date of compilation: 01.06.2021

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

|  |   |
|--|---|
| Physical state   | liquid  |
| Colour   | brown   |
| Odour  | characteristic  |
| Melting point/freezing point                             | <-15 °C at 101,3 kPa                                      |
| Boiling point or initial boiling point and boiling range | not determined  |
| Evaporation rate   | not determined  |
| Flammability   | this material is combustible, but will not ignite readily |
| Lower and upper explosion limit                          | 0,6 vol% - 6,5 vol%                                       |
| Flash point  | >200 °C   |
| Auto-ignition temperature                                | not determined  |
| pH (value)   | not determined  |
| Kinematic viscosity                                      | 320 mm <sup>2</sup> /s at 40 °C                           |
| Solubility(ies)  | not determined  |

Partition coefficient

|   |                                   |
|---|-----------------------------------|
| Partition coefficient n-octanol/water (log value) | this information is not available |
|---|-----------------------------------|

|                 |                |
|-----------------|----------------|
| Vapour pressure | not determined |
|-----------------|----------------|

Density and/or relative density

|         |                                  |
|---------|----------------------------------|
| Density | 0,895 g/cm <sup>3</sup> at 15 °C |
|---------|----------------------------------|

|                          |                       |
|--------------------------|-----------------------|
| Particle characteristics | not relevant (liquid) |
|--------------------------|-----------------------|

**Industrie-Getriebeöl CLP 320**

Version number: 1.0

Date of compilation: 01.06.2021

**9.2 Other information**

|  |   |
|--|---|
| Information with regard to physical hazard classes | hazard classes acc. to GHS (physical hazards): not relevant |
| Other safety characteristics                       | there is no additional information                          |

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

**10.2 Chemical stability**

See below "Conditions to avoid".

**10.3 Possibility of hazardous reactions**

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

**10.4 Conditions to avoid**

There are no specific conditions known which have to be avoided.

**10.5 Incompatible materials**

Oxidisers

**10.6 Hazardous decomposition products**

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification according to GHS (1272/2008/EC, CLP)**

Acute toxicity

Shall not be classified as acutely toxic.

| Acute toxicity estimate (ATE) of components of the mixture |          |                |           |
|--|----------|----------------|-----------|
| Name of substance  | CAS No   | Exposure route | ATE       |
| (Z)-octadec-9-enylamine                                    | 112-90-3 | oral           | 500 mg/kg |

| Acute toxicity of components of the mixture |          |                |          |              |         |
|---|----------|----------------|----------|--------------|---------|
| Name of substance                           | CAS No   | Exposure route | Endpoint | Value        | Species |
| 2,6-di-tert-butylphenol                     | 128-39-2 | oral           | LD50     | >5.000 mg/kg | rat     |

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

**Industrie-Getriebeöl CLP 320**

Version number: 1.0

Date of compilation: 01.06.2021

**Serious eye damage/eye irritation**

Shall not be classified as seriously damaging to the eye or eye irritant.

**Respiratory or skin sensitisation**

Contains 2,5-Bis(oktyldithio)-1,3,4-Thiadiazol. May produce an allergic reaction.

**Germ cell mutagenicity**

Shall not be classified as germ cell mutagenic.

**Carcinogenicity**

Shall not be classified as carcinogenic.

**Reproductive toxicity**

Shall not be classified as a reproductive toxicant.

**Specific target organ toxicity - single exposure**

Shall not be classified as a specific target organ toxicant (single exposure).

**Specific target organ toxicity - repeated exposure**

Shall not be classified as a specific target organ toxicant (repeated exposure).

**Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

**11.2 Information on other hazards**

There is no additional information.

**SECTION 12: Ecological information**

**12.1 Toxicity**

Acc. to 1272/2008/EC: Harmful to aquatic life with long lasting effects.  
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 2, obviously hazardous to water (Germany)

| Aquatic toxicity (acute) of components of the mixture |          |          |           |                       |               |
|---|----------|----------|-----------|-----------------------|---------------|
| Name of substance                                     | CAS No   | Endpoint | Value     | Species               | Exposure time |
| 2,6-di-tert-butylphenol                               | 128-39-2 | LC50     | 1,4 mg/l  | fish                  | 96 h          |
| 2,6-di-tert-butylphenol                               | 128-39-2 | EC50     | 0,45 mg/l | aquatic invertebrates | 48 h          |

| Aquatic toxicity (chronic) of components of the mixture |          |          |           |                       |               |
|---|----------|----------|-----------|-----------------------|---------------|
| Name of substance                                       | CAS No   | Endpoint | Value     | Species               | Exposure time |
| 2,6-di-tert-butylphenol                                 | 128-39-2 | LC50     | 1,1 mg/l  | fish                  | 7 d           |
| 2,6-di-tert-butylphenol                                 | 128-39-2 | EC50     | 0,14 mg/l | aquatic invertebrates | 21 d          |

**Biodegradation**

Data are not available.



## Industrie-Getriebeöl CLP 320

Version number: 1.0

Date of compilation: 01.06.2021

### 12.2 Persistence and degradability

| Degradability of components of the mixture |          |                  |                  |      |        |        |
|--|----------|------------------|------------------|------|--------|--------|
| Name of substance                          | CAS No   | Process          | Degradation rate | Time | Method | Source |
| 2,6-di-tert-butylphenol                    | 128-39-2 | oxygen depletion | ≥12 – ≤24 %      | 28 d |        | ECHA   |

### 12.3 Bioaccumulative potential

Data are not available.

| Bioaccumulative potential of components of the mixture |          |     |             |          |
|--|----------|-----|-------------|----------|
| Name of substance                                      | CAS No   | BCF | Log KOW     | BOD5/COD |
| 2,6-di-tert-butylphenol                                | 128-39-2 |     | 4,5 (24 °C) |          |

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Endocrine disrupting properties

Information on this property is not available.

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

Mineral-based non-chlorinated engine, gear and lubricating oils 13 02 05\*

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

**Industrie-Getriebeöl CLP 320**

Version number: 1.0

Date of compilation: 01.06.2021

**SECTION 14: Transport information**

- 14.1 UN number or ID number** not subject to transport regulations
- 14.2 UN proper shipping name** not relevant
- 14.3 Transport hazard class(es)** none
- 14.4 Packing group** not assigned
- 14.5 Environmental hazards** non-environmentally hazardous acc. to the dangerous goods regulations
- 14.6 Special precautions for user**  
There is no additional information.
- 14.7 Maritime transport in bulk according to IMO instruments**  
The cargo is not intended to be carried in bulk.

**Information for each of the UN Model Regulations**

**Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - additional information**

Not subject to ADR, RID and ADN.

**International Maritime Dangerous Goods Code (IMDG) - additional information**

Not subject to IMDG.

**International Civil Aviation Organization (ICAO-IATA/DGR) - additional information**

Not subject to ICAO-IATA.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**Relevant provisions of the European Union (EU)**

**VOC Deco-Paint Directive 2004/42/EC**

|             |     |
|-------------|-----|
| VOC content | 1 % |
|-------------|-----|

**Industrial Emissions Directive (IED)**

|             |     |
|-------------|-----|
| VOC content | 1 % |
|-------------|-----|

**National regulations (Austria)**

Ordinance on combustible liquids (VbF) not applicable (mass fraction of liquids with a flash point of more than 100° C or of solids is higher than 30 %)

**National regulations (Germany)**

**Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)**

Wassergefährdungsklasse, WGK 2 obviously hazardous to water (water hazard class)

**National regulations Switzerland**

**Ordinance on the incentive tax on volatile organic compounds (VOCV)**

The product is exempt from the tax. Product in which the VOC content does not exceed 3 per cent (% by weight).

**Industrie-Getriebeöl CLP 320**

Version number: 1.0

Date of compilation: 01.06.2021

**15.2 Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information**

**Abbreviations and acronyms**

| Abbr.           | Descriptions of used abbreviations  |
|-----------------|---|
| Acute Tox.      | Acute toxicity  |
| ADN             | Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) |
| ADR             | Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)                                       |
| Aquatic Acute   | Hazardous to the aquatic environment - acute hazard   |
| Aquatic Chronic | Hazardous to the aquatic environment - chronic hazard   |
| Asp. Tox.       | Aspiration hazard   |
| ATE             | Acute Toxicity Estimate   |
| BCF             | Bioconcentration factor   |
| BOD             | Biochemical Oxygen Demand   |
| CAS             | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)  |
| CLP             | Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures  |
| COD             | Chemical oxygen demand  |
| DGR             | Dangerous Goods Regulations (see IATA/DGR)  |
| DNEL            | Derived No-Effect Level   |
| EC50            | Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval                                      |
| EC No           | The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)                                     |
| EINECS          | European Inventory of Existing Commercial Chemical Substances   |
| ELINCS          | European List of Notified Chemical Substances   |
| Eye Dam.        | Seriously damaging to the eye   |
| Eye Irrit.      | Irritant to the eye   |
| GHS             | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations   |
| IATA            | International Air Transport Association   |
| IATA/DGR        | Dangerous Goods Regulations (DGR) for the air transport (IATA)  |
| ICAO            | International Civil Aviation Organization   |
| IMDG            | International Maritime Dangerous Goods Code   |
| index No        | The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008  |
| LC50            | Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval   |

**Industrie-Getriebeöl CLP 320**

Version number: 1.0

Date of compilation: 01.06.2021

| Abbr.       | Descriptions of used abbreviations   |
|-------------|--|
| LD50        | Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval   |
| log KOW     | n-Octanol/water  |
| M-factor    | Means a multiplying factor. It is applied to the concentration of a substance classified as hazardous to the aquatic environment acute category 1 or chronic category 1, and is used to derive by the summation method the classification of a mixture in which the substance is present |
| NLP         | No-Longer Polymer  |
| PBT         | Persistent, Bioaccumulative and Toxic  |
| PNEC        | Predicted No-Effect Concentration  |
| REACH       | Registration, Evaluation, Authorisation and Restriction of Chemicals   |
| RID         | Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)  |
| Skin Corr.  | Corrosive to skin  |
| Skin Irrit. | Irritant to skin   |
| Skin Sens.  | Skin sensitisation   |
| STOT RE     | Specific target organ toxicity - repeated exposure   |
| STOT SE     | Specific target organ toxicity - single exposure   |
| TRGS        | Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany)   |
| VOC         | Volatile Organic Compounds   |
| vPvB        | Very Persistent and very Bioaccumulative   |

**Key literature references and sources for data**

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

**Classification procedure**

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**List of relevant phrases (code and full text as stated in chapter 2 and 3)**

| Code | Text   |
|------|--|
| H302 | Harmful if swallowed.  |
| H304 | May be fatal if swallowed and enters airways.                      |
| H314 | Causes severe skin burns and eye damage.                           |
| H315 | Causes skin irritation.  |
| H317 | May cause an allergic skin reaction.                               |
| H319 | Causes serious eye irritation.                                     |
| H335 | May cause respiratory irritation.                                  |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

**Industrie-Getriebeöl CLP 320**

Version number: 1.0

Date of compilation: 01.06.2021

| Code | Text  |
|------|---|
| H400 | Very toxic to aquatic life.                           |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects.    |

**Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.