

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name **Condor Schneidöl RC 2**
Registration number (REACH) Not relevant (mixture)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Lubricants, greases, release products

1.3 Details of the supplier of the safety data sheet

FRIEDRICH SCHARR KG
Liebknechtstraße 50
70565 Stuttgart
Germany

Telephone: +49 711 7868-0
Telefax: +49 711 7868-489
e-mail: info@scharr.de
Website: www.scharr.de

e-mail (competent person) produktsicherheit@scharr.de

1.4 Emergency telephone number

Poison centre

Country	Name	Postal code/city	Telephone
Germany	Giftinformation Freiburg	79106 Freiburg im Breisgau	+49 (0)761 19240

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 (CLP)

This mixture does not meet the criteria for classification in accordance with Regulation No 1272/2008/EC.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)
not required

2.3 Other hazards

of no significance

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not relevant (mixture)




3.2 Mixtures

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022




Hazardous ingredients

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Distillates (petroleum), heavy hydrocracked	CAS No 64741-76-0 EC No 265-077-7 Index No 649-453-00-1 REACH Reg. No 01-2119486951-26-xxxx	35,04 – 91,57		
Distillates (petroleum), hydrotreated heavy paraffinic	CAS No 64742-54-7 EC No 265-157-1 Index No 649-467-00-8 REACH Reg. No 01-2119484627-25-xxxx	35,04 – 91,57		
Distillates (petroleum), hydrotreated light paraffinic	CAS No 64742-55-8 EC No 265-158-7 Index No 649-468-00-3 REACH Reg. No 01-2119487077-29-xxxx	10,1 – 26,5	Asp. Tox. 1 / H304	
Distillates (petroleum), hydrotreated heavy paraffinic	CAS No 64742-54-7 EC No 265-157-1 Index No 649-467-00-8 REACH Reg. No 01-2119484627-25-xxxx	0,48 – 3,528		
Haftzusatzpolymer		0,1 – 1,5		
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	CAS No 68442-22-8 EC No 270-478-5 REACH Reg. No 01-2119948548-22-xxxx	0,1 – 0,735	Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Aquatic Chronic 2 / H411	 

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivatives	CAS No 84605-20-9 EC No 617-593-2	0,05 – 0,49	Aquatic Chronic 4 / H413	
Kurz-, mittel- und langkettige Alkylmethacrylate Copolymer (ACC-ZX665225-90)		≤ 0,2542	Eye Irrit. 2 / H319	
Distillates (petroleum), hydrotreated light paraffinic	CAS No 64742-55-8 EC No 265-158-7 Index No 649-468-00-3 REACH Reg. No 01-2119487077-29-xxxx	≤ 0,09775	Asp. Tox. 1 / H304	
Distillates (petroleum), hydrotreated heavy paraffinic	CAS No 64742-54-7 EC No 265-157-1 Index No 649-467-00-8 REACH Reg. No 01-2119484627-25-xxxx	≤ 0,05865		
Distillates (petroleum), solvent-dewaxed heavy paraffinic	CAS No 64742-65-0 EC No 265-169-7 REACH Reg. No 01-2119471299-27-xxxx	≤ 0,05865	Asp. Tox. 1 / H304	

Name of substance	Specific Conc. Limits	M-Factors	ATE	Exposure route
Distillates (petroleum), hydrotreated light paraffinic	-	-	2,18 mg/l/4h	inhalation: dust/mist

Hazardous ingredients acc. to EU regulation, Consideration of other advice

This mixture does not meet the criteria for classification in accordance with Regulation No 1272/2008/EC.

For full text of abbreviations: see SECTION 16.

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Self-protection of the first aider.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulties. Headache. Vertigo.

4.3 Indication of any immediate medical attention and special treatment needed

Subsequent observance for pneumonia and pulmonary oedema. Supervise the blood circulation.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂), Sand

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Danger of bursting container.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Ventilate affected area. Avoidance of ignition sources.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Provision of sufficient ventilation.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

- Lagerklasse (storage class according to TRGS 510, 10 (combustible liquids) Germany)

7.3 Specific end use(s)

See section 16 for a general overview.

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

This information is not available.

Relevant DNELs of components of the mixture						
Name of sub-stance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	68442-22-8	DNEL	8,05 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	68442-22-8	DNEL	11,4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of sub-stance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Distillates (petroleum), heavy hydro-cracked	64741-76-0	PNEC	9,33 mg/kg	aquatic organisms	water	short-term (single instance)
Distillates (petroleum), hydro-treated heavy paraffinic	64742-54-7	PNEC	9,33 mg/kg	aquatic organisms	water	short-term (single instance)
Distillates (petroleum), hydro-treated light paraffinic	64742-55-8	PNEC	9,33 mg/kg	aquatic organisms	water	short-term (single instance)
Distillates (petroleum), hydro-treated heavy paraffinic	64742-54-7	PNEC	9,33 mg/kg	aquatic organisms	water	short-term (single instance)
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	68442-22-8	PNEC	4 µg/l	aquatic organisms	freshwater	short-term (single instance)
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	68442-22-8	PNEC	4,6 µg/l	aquatic organisms	marine water	short-term (single instance)
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	68442-22-8	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	68442-22-8	PNEC	0,045 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	68442-22-8	PNEC	0,005 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	68442-22-8	PNEC	0,007 mg/kg	terrestrial organisms	soil	short-term (single instance)
Distillates (petroleum), hydro-treated light paraffinic	64742-55-8	PNEC	9,33 mg/kg	aquatic organisms	water	short-term (single instance)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	PNEC	9,33 mg/kg	aquatic organisms	water	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- type of material

PE: polyethylene, CR: chloroprene (chlorobutadiene) rubber, IIR: isobutene-isoprene (butyl) rubber

- material thickness

> 0,35 mm

- breakthrough times of the glove material

0,4 mm

>120 minutes (permeation: level 4)

- other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

[In case of inadequate ventilation] wear respiratory protection. Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown).

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	yellow
Odour	characteristic
Melting point/freezing point	0 °C at 101,3 kPa
Boiling point or initial boiling point and boiling range	not determined
Evaporation rate	not determined
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	0,6 vol% - 6,5 vol%
Flash point	>200 °C
Auto-ignition temperature	>250 °C
pH (value)	not determined
Kinematic viscosity	24 mm ² /s at 40 °C
Solubility(ies)	not determined

Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	not determined
-----------------	----------------

Density and/or relative density

Density	0,859 g/cm ³ at 15 °C
---------	----------------------------------

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

9.2 Other information

Information with regard to physical hazard classes	hazard classes acc. to GHS (physical hazards): not relevant
Other safety characteristics	
Temperature class (EU, acc. to ATEX)	T3 (maximum permissible surface temperature on the equipment: 200°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

This mixture does not meet the criteria for classification in accordance with Regulation No 1272/2008/EC.

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	inhalation: dust/mist	2,18 mg/l/4h

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Distillates (petroleum), heavy hydro-cracked	64741-76-0	oral	LD50	>5.000 mg/kg	rat
Distillates (petroleum), heavy hydro-cracked	64741-76-0	inhalation: dust/mist	LC50	2,18 mg/l/4h	rat
Distillates (petroleum), heavy hydro-cracked	64741-76-0	dermal	LD50	>5.000 mg/kg	rabbit
Distillates (petroleum), hydro-treated heavy paraffinic	64742-54-7	oral	LD50	>5.000 mg/kg	rat
Distillates (petroleum), hydro-treated heavy paraffinic	64742-54-7	inhalation: dust/mist	LC50	2,18 mg/l/4h	rat
Distillates (petroleum), hydro-treated heavy paraffinic	64742-54-7	dermal	LD50	>5.000 mg/kg	rabbit
Distillates (petroleum), hydro-treated light paraffinic	64742-55-8	oral	LD50	>5.000 mg/kg	rat
Distillates (petroleum), hydro-treated light paraffinic	64742-55-8	inhalation: dust/mist	LC50	2,18 mg/l/4h	rat
Distillates (petroleum), hydro-treated light paraffinic	64742-55-8	dermal	LD50	>5.000 mg/kg	rabbit
Distillates (petroleum), hydro-treated heavy paraffinic	64742-54-7	oral	LD50	>5.000 mg/kg	rat
Distillates (petroleum), hydro-treated heavy paraffinic	64742-54-7	inhalation: dust/mist	LC50	2,18 mg/l/4h	rat
Distillates (petroleum), hydro-treated heavy paraffinic	64742-54-7	dermal	LD50	>5.000 mg/kg	rabbit
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	68442-22-8	oral	LD50	>2.000 – <5.000 mg/kg	rat
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	68442-22-8	dermal	LD50	>2.002 mg/kg	rat
Distillates (petroleum), hydro-treated heavy paraffinic	64742-54-7	oral	LD50	>5.000 mg/kg	rat
Distillates (petroleum), hydro-treated heavy paraffinic	64742-54-7	inhalation: dust/mist	LC50	2,18 mg/l/4h	rat
Distillates (petroleum), hydro-treated heavy paraffinic	64742-54-7	dermal	LD50	>5.000 mg/kg	rabbit
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	oral	LD50	>5.000 mg/kg	rat
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	inhalation: dust/mist	LC50	2,18 mg/l/4h	rat
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	dermal	LD50	>5.000 mg/kg	rabbit

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment.
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 1, slightly hazardous to water (Germany)

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), heavy hydrocracked	64741-76-0	LL50	>100 mg/l	fish	96 h
Distillates (petroleum), heavy hydrocracked	64741-76-0	EL50	>10.000 mg/l	aquatic invertebrates	24 h
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	LL50	>100 mg/l	fish	96 h
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	EL50	>10.000 mg/l	aquatic invertebrates	24 h
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	LL50	>100 mg/l	fish	96 h
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	EL50	>10.000 mg/l	aquatic invertebrates	24 h

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	LL50	>100 mg/l	fish	96 h
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	EL50	>10.000 mg/l	aquatic invertebrates	24 h
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	68442-22-8	LL50	4,5 mg/l	fish	96 h
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	68442-22-8	LC50	46 mg/l	fish	96 h
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	68442-22-8	EL50	23 mg/l	aquatic invertebrates	48 h
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	LL50	>100 mg/l	fish	96 h
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	LL50	>100 mg/l	fish	96 h
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	EL50	>10.000 mg/l	aquatic invertebrates	24 h
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	LL50	>100 mg/l	fish	96 h
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	EL50	>10.000 mg/l	aquatic invertebrates	24 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), heavy hydrocracked	64741-76-0	LL50	>10.000 mg/l	aquatic invertebrates	24 h
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	LL50	>10.000 mg/l	aquatic invertebrates	24 h
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	EL50	>10.000 mg/l	aquatic invertebrates	24 h
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	LL50	>10.000 mg/l	aquatic invertebrates	24 h

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	LL50	>10.000 mg/l	aquatic invertebrates	24 h
Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu) esters, zinc salts	68442-22-8	EC50	>10.000 mg/l	microorganisms	3 h
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	LL50	>10.000 mg/l	aquatic invertebrates	24 h
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	LL50	>10.000 mg/l	aquatic invertebrates	24 h

Biodegradation

Data are not available.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

Mineral-based machining oils free of halogens (except emulsions and solutions) 12 01 07*

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

SECTION 14: Transport information

- 14.1 UN number or ID number** not subject to transport regulations
- 14.2 UN proper shipping name** not relevant
- 14.3 Transport hazard class(es)** none
- 14.4 Packing group** not assigned
- 14.5 Environmental hazards** non-environmentally hazardous acc. to the dangerous goods regulations
- 14.6 Special precautions for user**
There is no additional information.
- 14.7 Maritime transport in bulk according to IMO instruments**
The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - additional information

Not subject to ADR, RID and ADN.

International Maritime Dangerous Goods Code (IMDG) - additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

none of the ingredients are listed

Seveso Directive

2012/18/EU (Seveso III)

No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
	not assigned		

VOC Deco-Paint Directive 2004/42/EC

VOC content	2,427 %
-------------	---------

Industrial Emissions Directive (IED)

VOC content	0,3337 %
-------------	----------

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Water Framework Directive (WFD)

List of pollutants (WFD)			
Name of substance	CAS No	Listed in	Remarks
Distillates (petroleum), hydrotreated heavy paraffinic		a)	

Legend

A) Indicative list of the main pollutants

Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

National regulations (Austria)

Ordinance on combustible liquids (VbF)

not applicable (mass fraction of liquids with a flash point of more than 100° C or of solids is higher than 30 %)

National regulations (Germany)

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK 1 slightly hazardous to water
(water hazard class)

National regulations Switzerland

Ordinance on the incentive tax on volatile organic compounds (VOCV)

The product is exempt from the tax. Product in which the VOC content does not exceed 3 per cent (% by weight).

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)
2.2	Labelling according to Regulation (EC) No 1272/2008 (CLP)	Labelling according to Regulation (EC) No 1272/2008 (CLP): not required
2.2	- signal word: not required	
2.2	- pictograms: not required	
2.2		- supplemental hazard information: change in the listing (table)

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

Section	Former entry (text/value)	Actual entry (text/value)
3.2		Hazardous ingredients: change in the listing (table)
3.2		Hazardous ingredients: change in the listing (table)
8.1		Relevant DNELs of components of the mixture: change in the listing (table)
8.1		Relevant PNECs of components of the mixture: change in the listing (table)
8.2	Type of material: NBR: acrylonitrile-butadiene rubber	Type of material: PE: polyethylene, CR: chloroprene (chlorobutadiene) rubber, IIR: isobutene-isoprene (butyl) rubber
8.2	Material thickness: 0,4 mm	Material thickness: > 0,35 mm
8.2	Breakthrough times of the glove material: >240 minutes (permeation: level 5)	Breakthrough times of the glove material: 0,4 mm >120 minutes (permeation: level 4)
8.2	Respiratory protection: In case of inadequate ventilation wear respiratory protection.	Respiratory protection: [In case of inadequate ventilation] wear respiratory protection. Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown).
11.1		Acute toxicity estimate (ATE) of components of the mixture: change in the listing (table)
11.1		Acute toxicity of components of the mixture: change in the listing (table)
11.1	Respiratory or skin sensitisation: Contains Amines, C12-14-tert-alkyl, reaction products with O,O-di-C1-14-alkyl hydrogen phosphorodithioate. May produce an allergic reaction.	Respiratory or skin sensitisation: Shall not be classified as a respiratory or skin sensitiser.
12.1		Aquatic toxicity (acute) of components of the mixture: change in the listing (table)
12.1		Aquatic toxicity (chronic) of components of the mixture: change in the listing (table)

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

Abbr.	Descriptions of used abbreviations
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
SVHC	Substance of Very High Concern
TRGS	Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Condor Schneidöl RC 2

Version number: 2.0
Replaces version of: 23.07.2021 (1)

Revision: 14.06.2022

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.