

Hydrauliköl HVLP 32

Version number: 2.0
Replaces version of: 31.05.2022 (1)

Revision: 01.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name **Hydrauliköl HVLP 32**
Registration number (REACH) Not relevant (mixture)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Lubricants, greases, release products

1.3 Details of the supplier of the safety data sheet

FRIEDRICH SCHARR KG
Liebknechtstraße 50
70565 Stuttgart
Germany

Telephone: +49 711 7868-0
Telefax: +49 711 7868-489
e-mail: info@scharr.de
Website: www.scharr.de

e-mail (competent person) produktsicherheit@scharr.de

1.4 Emergency telephone number

Poison centre

| Country | Name | Postal code/city | Telephone |
|---------|--------------------------|----------------------------|------------------|
| Germany | Giftinformation Freiburg | 79106 Freiburg im Breisgau | +49 (0)761 19240 |

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 (CLP)

This mixture does not meet the criteria for classification in accordance with Regulation No 1272/2008/EC.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)
not required

2.3 Other hazards

of no significance

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not relevant (mixture)



3.2 Mixtures

Hydrauliköl HVLP 32

Version number: 2.0
Replaces version of: 31.05.2022 (1)

Revision: 01.06.2022

Hazardous ingredients

| Name of substance | Identifier | Wt% | Classification acc. to GHS | Pictograms |
|---|--|-----------|----------------------------|---|
| Distillates (petroleum), hydrotreated light paraffinic | CAS No 64742-55-8 EC No 265-158-7 Index No 649-468-00-3 REACH Reg. No 01-2119487077-29-xxxx | 10 – < 25 | Asp. Tox. 1 / H304 |  |
| Distillates (petroleum), solvent-refined heavy paraffinic | CAS No 64741-88-4 EC No 265-090-8 Index No 649-454-00-7 REACH Reg. No 01-2119488706-23-xxxx | 1 – < 5 | Asp. Tox. 1 / H304 |  |

Hazardous ingredients acc. to EU regulation, Consideration of other advice

This mixture does not meet the criteria for classification in accordance with Regulation No 1272/2008/EC.

For full text of abbreviations: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Self-protection of the first aider.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Breathing difficulties. Headache. Vertigo.

4.3 Indication of any immediate medical attention and special treatment needed

Subsequent observance for pneumonia and pulmonary oedema. Supervise the blood circulation.

Hydrauliköl HVLP 32

Version number: 2.0
Replaces version of: 31.05.2022 (1)

Revision: 01.06.2022

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂), Sand

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Danger of bursting container.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety. Ventilate affected area. Avoidance of ignition sources.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Provision of sufficient ventilation.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Hydrauliköl HVLP 32

Version number: 2.0
Replaces version of: 31.05.2022 (1)

Revision: 01.06.2022

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

- Lagerklasse (storage class according to TRGS 510, 10 (combustible liquids) Germany)

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

This information is not available.

| Relevant PNECs of components of the mixture | | | | | | |
|---|------------|-----------|-----------------|-------------------|---------------------------|------------------------------|
| Name of sub-stance | CAS No | End-point | Threshold level | Organism | Environmental compartment | Exposure time |
| Distillates (petroleum), hydro-treated light paraffinic | 64742-55-8 | PNEC | 9,33 mg/kg | aquatic organisms | water | short-term (single instance) |
| Distillates (petroleum), solvent-refined heavy paraffinic | 64741-88-4 | PNEC | 9,33 mg/kg | aquatic organisms | water | short-term (single instance) |

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- type of material

PE: polyethylene, CR: chloroprene (chlorobutadiene) rubber, IIR: isobutene-isoprene (butyl) rubber

Hydrauliköl HVLP 32

Version number: 2.0
Replaces version of: 31.05.2022 (1)

Revision: 01.06.2022

- material thickness > 0,35 mm
- breakthrough times of the glove material 0,4 mm
>120 minutes (permeation: level 4)
- other protection measures
Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

[In case of inadequate ventilation] wear respiratory protection. Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|---|
| Physical state | liquid |
| Colour | amber |
| Odour | characteristic |
| Melting point/freezing point | <-30 °C |
| Boiling point or initial boiling point and boiling range | ≥207 °C at 101,3 kPa |
| Evaporation rate | not determined |
| Flammability | this material is combustible, but will not ignite readily |
| Lower and upper explosion limit | 0,6 vol% - 6,5 vol% |
| Flash point | not determined |
| Auto-ignition temperature | >310 °C |
| pH (value) | not determined |
| Kinematic viscosity | 32 mm ² /s at 40 °C |
| Solubility(ies) | not determined |

Partition coefficient

| | |
|---|-----------------------------------|
| Partition coefficient n-octanol/water (log value) | this information is not available |
|---|-----------------------------------|

| | |
|-----------------|-------------------|
| Vapour pressure | <0,1 hPa at 20 °C |
|-----------------|-------------------|

Hydrauliköl HVLP 32

Version number: 2.0
Replaces version of: 31.05.2022 (1)

Revision: 01.06.2022

Density and/or relative density

| | |
|---------|--------------------|
| Density | 0,85 kg/l at 15 °C |
|---------|--------------------|

| | |
|--------------------------|-----------------------|
| Particle characteristics | not relevant (liquid) |
|--------------------------|-----------------------|

9.2 Other information

| | |
|--|--|
| Information with regard to physical hazard classes | hazard classes acc. to GHS (physical hazards): not relevant |
|--|--|

Other safety characteristics

| | |
|--------------------------------------|--|
| Temperature class (EU, acc. to ATEX) | T2 (maximum permissible surface temperature on the equipment: 300°C) |
|--------------------------------------|--|

SECTION 10: Stability and reactivity**10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

This mixture does not meet the criteria for classification in accordance with Regulation No 1272/2008/EC.

Acute toxicity

Shall not be classified as acutely toxic.

Hydrauliköl HVLP 32

Version number: 2.0
Replaces version of: 31.05.2022 (1)

Revision: 01.06.2022

| Acute toxicity estimate (ATE) of components of the mixture | | | |
|--|------------|-----------------------|--------------|
| Name of substance | CAS No | Exposure route | ATE |
| Distillates (petroleum), hydrotreated light paraffinic | 64742-55-8 | inhalation: dust/mist | 2,18 mg/l/4h |

| Acute toxicity of components of the mixture | | | | | |
|---|------------|-----------------------|----------|--------------|---------|
| Name of substance | CAS No | Exposure route | Endpoint | Value | Species |
| Distillates (petroleum), hydro-treated light paraffinic | 64742-55-8 | oral | LD50 | >5.000 mg/kg | rat |
| Distillates (petroleum), hydro-treated light paraffinic | 64742-55-8 | inhalation: dust/mist | LC50 | 2,18 mg/l/4h | rat |
| Distillates (petroleum), hydro-treated light paraffinic | 64742-55-8 | dermal | LD50 | >5.000 mg/kg | rabbit |
| Distillates (petroleum), solvent-refined heavy paraffinic | 64741-88-4 | oral | LD50 | >5.000 mg/kg | rat |
| Distillates (petroleum), solvent-refined heavy paraffinic | 64741-88-4 | inhalation: dust/mist | LC50 | 2,18 mg/l/4h | rat |
| Distillates (petroleum), solvent-refined heavy paraffinic | 64741-88-4 | dermal | LD50 | >5.000 mg/kg | rabbit |

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

There is no additional information.

Hydrauliköl HVLP 32

Version number: 2.0
Replaces version of: 31.05.2022 (1)

Revision: 01.06.2022

SECTION 12: Ecological information

12.1 Toxicity

Acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment.
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV): WGK 1, slightly hazardous to water (Germany)

| Aquatic toxicity (acute) of components of the mixture | | | | | |
|---|------------|----------|--------------|-----------------------|---------------|
| Name of substance | CAS No | Endpoint | Value | Species | Exposure time |
| Distillates (petroleum), hydrotreated light paraffinic | 64742-55-8 | LL50 | >100 mg/l | fish | 96 h |
| Distillates (petroleum), hydrotreated light paraffinic | 64742-55-8 | EL50 | >10.000 mg/l | aquatic invertebrates | 24 h |
| Distillates (petroleum), solvent-refined heavy paraffinic | 64741-88-4 | LL50 | >100 mg/l | fish | 96 h |
| Distillates (petroleum), solvent-refined heavy paraffinic | 64741-88-4 | EL50 | >10.000 mg/l | aquatic invertebrates | 24 h |

| Aquatic toxicity (chronic) of components of the mixture | | | | | |
|---|------------|----------|--------------|-----------------------|---------------|
| Name of substance | CAS No | Endpoint | Value | Species | Exposure time |
| Distillates (petroleum), hydrotreated light paraffinic | 64742-55-8 | LL50 | >10.000 mg/l | aquatic invertebrates | 24 h |
| Distillates (petroleum), solvent-refined heavy paraffinic | 64741-88-4 | LL50 | >10.000 mg/l | aquatic invertebrates | 24 h |

Biodegradation

Data are not available.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Information on this property is not available.

12.7 Other adverse effects

Data are not available.

Hydrauliköl HVLP 32

Version number: 2.0
Replaces version of: 31.05.2022 (1)

Revision: 01.06.2022

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

Mineral based non-chlorinated hydraulic oils 13 01 10*

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

- | | | |
|------|---|---|
| 14.1 | UN number or ID number | not subject to transport regulations |
| 14.2 | UN proper shipping name | not relevant |
| 14.3 | Transport hazard class(es) | none |
| 14.4 | Packing group | not assigned |
| 14.5 | Environmental hazards | non-environmentally hazardous acc. to the dangerous goods regulations |
| 14.6 | Special precautions for user | There is no additional information. |
| 14.7 | Maritime transport in bulk according to IMO instruments | The cargo is not intended to be carried in bulk. |

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - additional information

Not subject to ADR, RID and ADN.

International Maritime Dangerous Goods Code (IMDG) - additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - additional information

Not subject to ICAO-IATA.

Hydrauliköl HVLP 32

Version number: 2.0
Replaces version of: 31.05.2022 (1)

Revision: 01.06.2022

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

VOC Deco-Paint Directive 2004/42/EC

| | |
|-------------|-----|
| VOC content | 0 % |
|-------------|-----|

Industrial Emissions Directive (IED)

| | |
|-------------|-----|
| VOC content | 0 % |
|-------------|-----|

National regulations (Austria)

Ordinance on combustible liquids (VbF) not applicable (mass fraction of liquids with a flash point of more than 100° C or of solids is higher than 30 %)

National regulations (Germany)

Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (Ordinance on facilities for handling substances hazardous to water) (AwSV)

Wassergefährdungsklasse, WGK 1 slightly hazardous to water
(water hazard class)

National regulations Switzerland

Ordinance on the incentive tax on volatile organic compounds (VOCV)

The product is exempt from the tax. Product in which the VOC content does not exceed 3 per cent (% by weight).

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

| Section | Former entry (text/value) | Actual entry (text/value) |
|---------|---|--|
| 3.2 | | Hazardous ingredients: change in the listing (table) |
| 8.2 | Type of material: NBR: acrylonitrile-butadiene rubber | Type of material: PE: polyethylene, CR: chloroprene (chlorobutadiene) rubber, IIR: isobutene-isoprene (butyl) rubber |
| 8.2 | Material thickness: 0,4 mm | Material thickness: > 0,35 mm |
| 8.2 | Breakthrough times of the glove material: >240 minutes (permeation: level 5) | Breakthrough times of the glove material: 0,4 mm >120 minutes (permeation: level 4) |
| 8.2 | Protective gloves Splash protection | |
| 8.2 | Type of material: nitrile | |
| 8.2 | Respiratory protection: In case of inadequate ventilation wear respiratory protection. | Respiratory protection: [In case of inadequate ventilation] wear respiratory protection. Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown). |

Hydrauliköl HVLP 32

Version number: 2.0
Replaces version of: 31.05.2022 (1)

Revision: 01.06.2022

| Section | Former entry (text/value) | Actual entry (text/value) |
|---------|---------------------------|---|
| 11.1 | | Acute toxicity of components of the mixture: change in the listing (table) |

Abbreviations and acronyms

| Abbr. | Descriptions of used abbreviations |
|-----------|---|
| ADN | Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways) |
| ADR | Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road) |
| Asp. Tox. | Aspiration hazard |
| ATE | Acute Toxicity Estimate |
| CAS | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances) |
| CLP | Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures |
| DGR | Dangerous Goods Regulations (see IATA/DGR) |
| EC No | The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union) |
| EINECS | European Inventory of Existing Commercial Chemical Substances |
| EL50 | Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms |
| ELINCS | European List of Notified Chemical Substances |
| GHS | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations |
| IATA | International Air Transport Association |
| IATA/DGR | Dangerous Goods Regulations (DGR) for the air transport (IATA) |
| ICAO | International Civil Aviation Organization |
| IMDG | International Maritime Dangerous Goods Code |
| index No | The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 |
| LC50 | Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval |
| LD50 | Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval |
| LL50 | Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality |
| NLP | No-Longer Polymer |
| PBT | Persistent, Bioaccumulative and Toxic |
| PNEC | Predicted No-Effect Concentration |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals |
| RID | Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail) |

Hydrauliköl HVLP 32

Version number: 2.0
Replaces version of: 31.05.2022 (1)

Revision: 01.06.2022

| Abbr. | Descriptions of used abbreviations |
|-------|--|
| TRGS | Technische Regeln für Gefahrstoffe (technical rules for hazardous substances, Germany) |
| VOC | Volatile Organic Compounds |
| vPvB | Very Persistent and very Bioaccumulative |

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

| Code | Text |
|------|---|
| H304 | May be fatal if swallowed and enters airways. |

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.