

Drivolin Superior HD S3 SAE 10W-40

Description

Multigrade motor oil with high performance and a wide range of applications.

Area of use

Excellent for use in a mixed fleet - for diesel engines with and without turbochargers as well as for gasoline engines. Suitable for year-round use due to the favorable viscosity class. Can also be used for hydraulics and hydrostatic drives if the manufacturer's instructions are observed.

Benefits

- excellent cleaning effect
- excellent wear protection
- good shear stability
- oxidations- und alterungsstabil
- reliable protection against corrosion and black sludge

Specification

- API CF-4/SF
- ACEA E2
- MB-Blatt 228.1
- MTU-1

Typical parameters

Property	Test specification	Dimension	Typical values
density at 15 °C	DIN 51757	kg/m ³	865
kinematic viscosity at 40 °C	DIN 51562	mm ² /s	87,0
kinematic viscosity at 100 °C	DIN 51562	mm ² /s	13
viscosity index	DIN ISO 2909	-	> 140
flash point (COC)	DIN ISO 2592	°C	> 200
Pour point	DIN ISO 3016	°C	< -20

date of compilation 2020-10-29

No liability is assumed for the correctness and completeness of the information in this product information. The data provided are for guidance only. It is the user's responsibility to use the products with caution and to observe the applicable laws and regulations. Our general terms of delivery, in particular the liability provisions contained therein, apply to all deliveries. Subject to change. The specified data however does not release you from your obligation to inspect the incoming goods.

FRIEDRICH SCHARR KG

Liebkechtstraße 50 • 70565 Stuttgart • telephone: +49 711 7868-0 • telefax: +49 711 7868-489 • info@scharr.de • www.scharr.de